## Sullivan Palatek.

## **OIL ANALYSIS REPORT**

RAGE U46 SULLAIR 003-85053 - MALNOVE

Component Compressor

Area

### DIAGNOSIS

#### Recommendation

The filter change at the time of sampling has been noted. Resample at the next service interval to monitor. Please specify the brand, type, and viscosity of the oil on your next sample.

#### Wear


All component wear rates are normal.

#### Contamination

Moderate concentration of visible dirt/debris present in the oil.

#### Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is acceptable for the time in service.



Sample Rating Trend




SAMPLE INFORM	IATION	method	limit/base	current	history1	history2
Sample Number		Client Info		UCS06214851	UCS06103153	
Sample Date		Client Info		10 Jun 2024	20 Feb 2024	
Machine Age	hrs	Client Info		48583	48553	
Oil Age	hrs	Client Info		30	2500	
Oil Changed		Client Info		Not Changd	Changed	
Sample Status				NORMAL	NORMAL	
CONTAMINATION	٧	method	limit/base	current	history1	history2
Water		WC Method	>0.1	NEG	NEG	
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	0	0	
Chromium	ppm	ASTM D5185m	>10	0	0	
Nickel	ppm	ASTM D5185m		0	0	
Titanium	ppm	ASTM D5185m		0	0	
Silver	ppm	ASTM D5185m		0	0	
Aluminum	ppm	ASTM D5185m	>25	<1	0	
Lead	ppm	ASTM D5185m	>25	0	0	
Copper	ppm	ASTM D5185m		<1	0	
Tin	ppm	ASTM D5185m	>15	<1	<1	
Vanadium	ppm	ASTM D5185m		0	<1	
Cadmium	ppm	ASTM D5185m		0	0	
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0	<1	
Barium	ppm	ASTM D5185m		3	3	
Molybdenum	ppm	ASTM D5185m		0	0	
Manganese	ppm	ASTM D5185m		<1	0	
Magnesium	ppm	ASTM D5185m		0	<1	
Calcium	ppm	ASTM D5185m		0	0	
Phosphorus	ppm	ASTM D5185m		192	9	
Zinc	ppm	ASTM D5185m		0	0	
Sulfur	ppm	ASTM D5185m		715	46	
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	<1	3	
Sodium	ppm	ASTM D5185m		1	<1	
Potassium	ppm	ASTM D5185m	>20	2	0	
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045		0.39	0.33	



# **OIL ANALYSIS REPORT**

VISUAL



	VISUAL		methou				
	White Metal	scalar	*Visual	NONE	NONE	NONE	
	Yellow Metal	scalar	*Visual	NONE	NONE	NONE	
	Precipitate	scalar	*Visual	NONE	NONE	NONE	
	Silt	scalar	*Visual	NONE	NONE	NONE	
	Debris	scalar	*Visual	NONE	MODER	NONE	
	Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	
/24	Appearance	scalar	*Visual	NORML	NORML	NORML	
Jun 10/24	Odor	scalar	*Visual	NORML	NORML	NORML	
	Emulsified Water	scalar	*Visual	>0.1	NEG	NEG	
	Free Water	scalar	*Visual	20.1	NEG	NEG	
	FLUID PROPERT		method	limit/base	current	history1	history2
	Visc @ 40°C	cSt	ASTM D445		44.3	50.3	
	SAMPLE IMAGE	S	method	limit/base	current	history1	history2
Jun1024 +	Color				A		no image
	Bottom						no image
	GRAPHS						
	Ferrous Alloys						
	<sup>10</sup>						
	8 - iron chromium						
	E 6						
	4						
	2						
	1/24			1/24			
	Feb 20/24			Jun 10/24			
	Non-ferrous Meta	le		->			
	8 - copper						
	C tin						
	d 4						
	2-						
	0			24			
	Feb 20/24			Jun10/24			
				лг			
	Viscosity @ 40°C				Acid Number		
	Abnormal			( <sup>D</sup> ).40			
	50 -			(b)HO B)HO Mump U U U U U U U U U U U U U U U U U U U			
	(J. 04) 45 - 75			<u>الج</u> 0.20			
	40 Abnormal			- 20,10			
	35						
				0.00			
	Feb20/24			Jun 10/24	Feb 20/24		
Laboratory Sample No. Lab Number	: WearCheck USA - 50 : UCS06214851 : 06214851 : 11087715	1 Madiso Recei Teste Diagn	ved : 19 d : 20	, NC 27513 ) Jun 2024 ) Jun 2024 Jun 2024 - Sea			

Contact/Location: CHASE SVOBODA - UCRASWAT