

OIL ANALYSIS REPORT

Sample Rating Trend



Machine Id

EISENBEISS L-5

Component Distribution Gear Fluid MOBIL SHC 634 (--- GAL)

DIAGNOSIS

A Recommendation

We advise that you check all areas where dirt can enter the system. Resample at the next service interval to monitor.

🛑 Wear

All component wear rates are normal.

Contamination

Elemental levels of silicon (Si) and aluminum (Al) indicate alumina-silicate (coarse dirt) ingress.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

SAIVIELE INFORM	ATION	method	iimi/base	current	TIIStory I	riistory2
Sample Number		Client Info		WC0906974		
Sample Date		Client Info		03 Jun 2024		
Machine Age	mths	Client Info		0		
Oil Age	mths	Client Info		22		
Oil Changed		Client Info		N/A		
Sample Status				ABNORMAL		
WEAR METALS		method	limit/base	current	history1	history2
PQ		ASTM D8184	>200	19		
Iron	ppm	ASTM D5185m	>300	22		
Chromium	ppm	ASTM D5185m	>3	0		
Nickel	ppm	ASTM D5185m	>10	<1		
Titanium	ppm	ASTM D5185m		<1		
Silver	ppm	ASTM D5185m		0		
Aluminum	ppm	ASTM D5185m	>5	9		
Lead	ppm	ASTM D5185m	>60	0		
Copper	ppm	ASTM D5185m	>35	0		
Tin	ppm	ASTM D5185m	>5	0		
Vanadium	ppm	ASTM D5185m		0		
Cadmium	ppm	ASTM D5185m		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		<1		
Barium	ppm	ASTM D5185m		0		
Molybdenum	ppm	ASTM D5185m		0		
Manganese	ppm	ASTM D5185m		<1		
Magnesium	ppm	ASTM D5185m		3		
Calcium	ppm	ASTM D5185m		6		
Phosphorus	ppm	ASTM D5185m		495		
Zinc	ppm	ASTM D5185m		0		
Sulfur	ppm	ASTM D5185m		72		
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	<u> </u>		
Sodium	ppm	ASTM D5185m		2		
Potassium	ppm	ASTM D5185m	>20	2		
Water	%	ASTM D6304	>0.2	NEG		
FLUID DEGRADA		method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045		0.67		



OIL ANALYSIS REPORT



Contact/Location: EARL WILBANKS - DIAPLALA