


# **OIL ANALYSIS REPORT**

Sample Rating Trend

CMSI-B [S-25130]
ATLAS COPCO AIF123492 - POET NM SOUTH





## DIAGNOSIS

Component Compressor

### Recommendation

Resample at the next service interval to monitor.

#### Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the oil


## **Fluid Condition**

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

SAMPLE INFORM	MATION	method	limit/base	current	history1	history2	
Sample Number		Client Info		UCH06215836	UCH06113057	UCH06023852	
Sample Date		Client Info		13 Jun 2024	01 Mar 2024	28 Nov 2023	
Machine Age	hrs	Client Info		100073	97590	95332	
Oil Age	hrs	Client Info		6771	4288 2029		
Oil Changed		Client Info		Not Changd Not Change		Not Changd	
Sample Status				NORMAL	NORMAL	NORMAL	
CONTAMINATION		method	limit/base	current	history1	history2	
Water		WC Method	>0.1	NEG	NEG	NEG	
WEAR METALS		method	limit/base	current	history1	history2	
Iron	ppm	ASTM D5185m	>50	0	<1	0	
Chromium	ppm	ASTM D5185m	>5	0	0	0	
Nickel	ppm	ASTM D5185m		<1	0	0	
Titanium	ppm	ASTM D5185m		0	0	0	
Silver	ppm	ASTM D5185m		0	0	0	
Aluminum	ppm	ASTM D5185m	>15	<1	0	0	
Lead	ppm	ASTM D5185m	>65	0	0	0	
Copper	ppm	ASTM D5185m	>65	7	2	4	
Tin	ppm	ASTM D5185m	>10	<1	0	0	
Vanadium	ppm	ASTM D5185m		0	0	0	
Cadmium	ppm	ASTM D5185m		0	0	0	
ADDITIVES		method	limit/base	current	history1	history2	
Boron	ppm	ASTM D5185m	0.1	0	0	0	
Barium	ppm	ASTM D5185m	0.8	5	0	0	
Molybdenum	ppm	ASTM D5185m	0	0	0	0	
Manganese	ppm	ASTM D5185m	0.9	<1	0	0	
Magnesium	ppm	ASTM D5185m	0	<1	0	0	
Calcium	ppm	ASTM D5185m	0	<1	0	0	
Phosphorus	ppm	ASTM D5185m	409	180	197	261	
Zinc	ppm	ASTM D5185m	0	39	30	69	
Sulfur	ppm	ASTM D5185m	1290	517	571	792	
CONTAMINANTS		method	limit/base	current	history1	history2	
Silicon	ppm	ASTM D5185m	>35	<1	0	0	
Sodium	ppm	ASTM D5185m		2	0	0	
Potassium	ppm	ASTM D5185m	>20	4	0	0	
FLUID DEGRADA	TION	method	limit/base	current	history1	history2	
Acid Number (AN)	mg KOH/g	ASTM D8045	0.537	0.52	0.43	0.35	



# **OIL ANALYSIS REPORT**



VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
<b>Emulsified Water</b>	scalar	*Visual	>0.1	NEG	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG	NEG
ELLIID DBODED	TIEC	mothod	limit/basa	current	history1	history?


FLUID PROPER	THES	method			riistory i	riistoryz
Visc @ 40°C	cSt	ASTM D445	44.56	45.3	45.1	44.3


SAMPLE IMAGES


Color


**Bottom** 















Certificate 12367

Laboratory Sample No.

Test Package : IND 2

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 : UCH06215836 Lab Number : 06215836 Unique Number : 11088700

Received : 20 Jun 2024 **Tested** 

: 21 Jun 2024 Diagnosed : 21 Jun 2024 - Wes Davis **CAPITAL MACHINERY SYSTEMS** 

3207 W ANGLE ROAD PENDELTON, IN US 46064

Contact: BRIAN CALDWELL bcaldwell@capital-compressor.com

To discuss this sample report, contact Customer Service at 1-800-237-1369. \* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012) F: (765)788-0919

T: