

OIL ANALYSIS REPORT

Area MINING Machine Id JOHN DEERE ME-71

Front Differential Fluid SHELL Spirax S4 CX 30 (--- GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear


All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The condition of the oil is acceptable for the time in service.





NORMAL


SAMPLE INFORM	IATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0939947		
Sample Date		Client Info		18 Jun 2024		
Machine Age	hrs	Client Info		3250		
Oil Age	hrs	Client Info		0		
Oil Changed		Client Info		N/A		
Sample Status				NORMAL		
CONTAMINATION	٧	method	limit/base	current	history1	history2
Water		WC Method	>.2	NEG		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>500	16		
Chromium	ppm	ASTM D5185m	>10	<1		
Nickel	ppm	ASTM D5185m	>10	0		
Titanium	ppm	ASTM D5185m		<1		
Silver	ppm	ASTM D5185m		<1		
Aluminum	ppm	ASTM D5185m	>25	2		
Lead	ppm	ASTM D5185m	>25	8		
Copper	ppm	ASTM D5185m	>100	2		
Tin	ppm	ASTM D5185m	>10	0		
Vanadium	ppm	ASTM D5185m		0		
Cadmium	ppm	ASTM D5185m		<1		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		10		
Barium	ppm	ASTM D5185m		<1		
Molybdenum	ppm	ASTM D5185m		6		
Manganese	ppm	ASTM D5185m		<1		
Magnesium	ppm	ASTM D5185m		116		
Calcium	ppm	ASTM D5185m		3376		
Phosphorus	ppm	ASTM D5185m		1106		
Zinc	ppm	ASTM D5185m		1304		
Sulfur	ppm	ASTM D5185m		3916		
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>75	4		
Sodium	ppm	ASTM D5185m		0		
Potassium	ppm	ASTM D5185m		2		
VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE		
Yellow Metal	scalar	*Visual	NONE	NONE		
		*) // 1	NONE	NONE		
Precipitate	scalar	*Visual	NONL	NONE		
Precipitate Silt	scalar scalar	*Visual *Visual	NONE	NONE		
Silt	scalar	*Visual	NONE	NONE		
Silt Debris	scalar scalar	*Visual *Visual	NONE NONE	NONE NONE		
Silt Debris Sand/Dirt	scalar scalar scalar	*Visual *Visual *Visual	NONE NONE NONE	NONE NONE NONE		
Silt Debris Sand/Dirt Appearance	scalar scalar scalar scalar	*Visual *Visual *Visual *Visual	NONE NONE NORML	NONE NONE NONE NORML	 	

Report Id: COVLES [WUSCAR] 06216144 (Generated: 06/23/2024 16:46:28) Rev: 1

Submitted By: Grant Wilson Page 1 of 2



OIL ANALYSIS REPORT



FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 40°C cSt	ASTM D445	93.9	51.7		
SAMPLE IMAGES	method	limit/base	current	history1	history2
Color			no image	no image	no image
Bottom			no image	no image	no image
GRAPHS					
Ferrous Alloys					
16 iron					
14 * **********************************					
10-					
<u>۾</u> 8-					
6					
4					
2					
		4			
Jun 18/24		Jun 18/24			
⊸ Non-ferrous Metals		7			
9 _ copper sessesses lead 8 -					
7-					
6					
Ē 5-					
3					
2					
Jun 18/24		Jun18/24			
Jun1		Jun1			
Viscosity @ 40°C					
160 Abnormal					
140					
130					
ට 110 66 වි දි 100 Base					
ਤੋਂ 100 - B ase					
90 - Abnormal					
70 -					
60 - 50 -					
		8/24			
Jun 18/24		Jun 18/24			
: WearCheck USA - 501 Madisor			COVI	A - OTTAWA -L	ESUEUR - 0
: WC0939947 Receiv	ved : 20	Jun 2024	COVI	39770 C	TTAWA ROA
	ved : 20 d : 21			39770 C L	ESUEUR - 0 TTAWA ROA E SUEUR, M IS 56058-42

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Report Id: COVLES [WUSCAR] 06216144 (Generated: 06/23/2024 16:46:28) Rev: 1

Certificate L2367

T: (507)931-6081

F: