


# **OIL ANALYSIS REPORT**

Sample Rating Trend



Machine Id

# KAESER SM 8 2148829 (S/N 1075)

Component Compressor

KAESER SIGMA (OEM) M-460 (--- GAL)

### **DIAGNOSIS**

#### Recommendation

No corrective action is recommended at this time. Oil and filter change at the time of sampling has been noted. Resample at the next service interval to monitor.

#### Wear

All component wear rates are normal.

## Contamination

There is a high amount of particulates present in the oil.

#### **Fluid Condition**

The AN level is acceptable for this fluid. The condition of the oil is acceptable for the time in service.

|                  |          | Jan2017 1    | Mar2018 Oct2019 | Jan 2021 Mar 2022 Jun 2023 | Jun2024           |             |
|------------------|----------|--------------|-----------------|----------------------------|-------------------|-------------|
| SAMPLE INFORM    | MATION   | method       | limit/base      | current                    | history1          | history2    |
| Sample Number    |          | Client Info  |                 | KCPA018621                 | KCPA011838        | KCPA001960  |
| Sample Date      |          | Client Info  |                 | 06 Jun 2024                | 07 Dec 2023       | 08 Jun 2023 |
| Machine Age      | hrs      | Client Info  |                 | 84717                      | 82152             | 78476       |
| Oil Age          | hrs      | Client Info  |                 | 2575                       | 0                 | 0           |
| Oil Changed      |          | Client Info  |                 | Changed                    | N/A               | N/A         |
| Sample Status    |          |              |                 | ABNORMAL                   | ABNORMAL          | ATTENTION   |
| WEAR METALS      |          | method       | limit/base      | current                    | history1          | history2    |
| Iron             | ppm      | ASTM D5185m  | >50             | 1                          | 0                 | 0           |
| Chromium         | ppm      | ASTM D5185m  | >10             | <1                         | 0                 | 0           |
| Nickel           | ppm      | ASTM D5185m  | >3              | <1                         | 0                 | 0           |
| Titanium         | ppm      | ASTM D5185m  | >3              | <1                         | 0                 | 0           |
| Silver           | ppm      | ASTM D5185m  | >2              | <1                         | 0                 | 0           |
| Aluminum         | ppm      | ASTM D5185m  | >10             | 3                          | 0                 | 0           |
| Lead             | ppm      | ASTM D5185m  | >10             | <1                         | 0                 | 0           |
| Copper           | ppm      | ASTM D5185m  | >50             | 2                          | 1                 | 1           |
| Tin              | ppm      | ASTM D5185m  | >10             | <1                         | 0                 | 0           |
| Vanadium         | ppm      | ASTM D5185m  |                 | <1                         | <1                | <1          |
| Cadmium          | ppm      | ASTM D5185m  |                 | <1                         | 0                 | 0           |
| ADDITIVES        |          | method       | limit/base      | current                    | history1          | history2    |
| Boron            | ppm      | ASTM D5185m  | 0               | 0                          | 0                 | 0           |
| Barium           | ppm      | ASTM D5185m  | 90              | 44                         | 0                 | 28          |
| Molybdenum       | ppm      | ASTM D5185m  | 0               | <1                         | 0                 | 0           |
| Manganese        | ppm      | ASTM D5185m  |                 | <1                         | 0                 | 0           |
| Magnesium        | ppm      | ASTM D5185m  | 100             | 62                         | 0                 | 62          |
| Calcium          | ppm      | ASTM D5185m  | 0               | 0                          | 0                 | 0           |
| Phosphorus       | ppm      | ASTM D5185m  | 0               | 2                          | 0                 | 0           |
| Zinc             | ppm      | ASTM D5185m  | 0               | 8                          | 0                 | 0           |
| Sulfur           | ppm      | ASTM D5185m  | 23500           | 20355                      | 18061             | 21707       |
| CONTAMINANTS     |          | method       | limit/base      | current                    | history1          | history2    |
| Silicon          | ppm      | ASTM D5185m  | >25             | 2                          | <1                | <1          |
| Sodium           | ppm      | ASTM D5185m  |                 | 11                         | 19                | 10          |
| Potassium        | ppm      | ASTM D5185m  | >20             | 4                          | 2                 | <1          |
| Water            | %        | ASTM D6304   | >0.05           | 0.029                      | 0.015             | 0.029       |
| ppm Water        | ppm      | ASTM D6304   | >500            | 294                        | 154               | 297.0       |
| FLUID CLEANLIN   | ESS      | method       | limit/base      | current                    | history1          | history2    |
| Particles >4µm   |          | ASTM D7647   |                 | 152951                     | 6521              | 5743        |
| Particles >6µm   |          | ASTM D7647   | >1300           | <u> </u>                   | 2195              | 1796        |
| Particles >14μm  |          | ASTM D7647   | >80             | <b>16086</b>               | <u>179</u>        | 85          |
| Particles >21µm  |          | ASTM D7647   | >20             | <b>A</b> 3183              | <u>44</u>         | <b>1</b> 9  |
| Particles >38µm  |          | ASTM D7647   | >4              | <b>4</b> 34                | 2                 | 5           |
| Particles >71µm  |          | ASTM D7647   | >3              | 1                          | 0                 | 3           |
| Oil Cleanliness  |          | ISO 4406 (c) | >/17/13         | <b>24/24/21</b>            | <u>^</u> 20/18/15 | 0 20/18/14  |
| FLUID DEGRADA    | TION     | method       | limit/base      | current                    | history1          | history2    |
| Acid Number (AN) | mg KOH/g | ASTM D8045   | 1.0             | 0.37                       | 0.34              | 0.42        |



## **OIL ANALYSIS REPORT**







Certificate 12367

Laboratory Sample No.

Lab Number : 06216924

: KCPA018621 Unique Number: 11089788

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Received : 21 Jun 2024

**Tested** : 24 Jun 2024 Diagnosed

: 24 Jun 2024 - Don Baldridge

Test Package : IND 2 ( Additional Tests: KF, PrtCount ) To discuss this sample report, contact Customer Service at 1-800-237-1369.

 $^st$  - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Contact: SERVICE MANAGER T:

**DCS - DATA CENTER SYSTEMS** 

1881 VALLEY VIEW LN

FARMERS BRANCH, TX

US 75234

F: