




# OIL ANALYSIS REPORT

Area  
**SCHTRUCK**  
 Machine Id  
**6294 [SCHTRUCK]**  
 Component  
**Front Diesel Engine**  
 Fluid  
**PETRO CANADA DURON SHP 15W40 (--- GAL)**

Sample Rating Trend



## DIAGNOSIS

**Recommendation**  
 Resample at the next service interval to monitor.

**Wear**  
 All component wear rates are normal.

**Contamination**  
 There is no indication of any contamination in the oil.

**Fluid Condition**  
 The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION		method	limit/base	current	history1	history2
Sample Number	Client Info			<b>SBP0007710</b>	SBP0005964	SBP0004686
Sample Date	Client Info			<b>13 Jun 2024</b>	06 Dec 2023	28 Jun 2023
Machine Age	mls Client Info			<b>414002</b>	375358	399664
Oil Age	mls Client Info			<b>39045</b>	36198	39236
Oil Changed	Client Info			<b>Changed</b>	Changed	Changed
Sample Status				<b>NORMAL</b>	NORMAL	NORMAL

CONTAMINATION		method	limit/base	current	history1	history2
Fuel	WC Method	>5		<b>&lt;1.0</b>	<1.0	<1.0
Water	WC Method	>0.2		<b>NEG</b>	NEG	NEG
Glycol	WC Method			<b>NEG</b>	NEG	NEG

WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>80	<b>18</b>	16	21
Chromium	ppm	ASTM D5185m	>5	<b>&lt;1</b>	2	1
Nickel	ppm	ASTM D5185m	>2	<b>&lt;1</b>	<1	<1
Titanium	ppm	ASTM D5185m		<b>0</b>	<1	0
Silver	ppm	ASTM D5185m	>3	<b>0</b>	0	0
Aluminum	ppm	ASTM D5185m	>30	<b>8</b>	4	10
Lead	ppm	ASTM D5185m	>30	<b>0</b>	<1	0
Copper	ppm	ASTM D5185m	>150	<b>7</b>	8	10
Tin	ppm	ASTM D5185m	>5	<b>&lt;1</b>	<1	<1
Vanadium	ppm	ASTM D5185m		<b>0</b>	0	0
Cadmium	ppm	ASTM D5185m		<b>0</b>	<1	0

ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	0	<b>3</b>	0	4
Barium	ppm	ASTM D5185m	0	<b>0</b>	12	2
Molybdenum	ppm	ASTM D5185m	60	<b>64</b>	62	61
Manganese	ppm	ASTM D5185m	0	<b>&lt;1</b>	<1	<1
Magnesium	ppm	ASTM D5185m	1010	<b>1052</b>	961	810
Calcium	ppm	ASTM D5185m	1070	<b>1158</b>	1086	1252
Phosphorus	ppm	ASTM D5185m	1150	<b>1119</b>	1028	958
Zinc	ppm	ASTM D5185m	1270	<b>1382</b>	1241	1150
Sulfur	ppm	ASTM D5185m	2060	<b>3139</b>	2693	2659

CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>20	<b>4</b>	4	4
Sodium	ppm	ASTM D5185m		<b>3</b>	0	0
Potassium	ppm	ASTM D5185m	>20	<b>8</b>	6	12


INFRA-RED		method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844	>3	<b>0.8</b>	0.7	0.4
Nitration	Abs/cm	*ASTM D7624	>20	<b>9.2</b>	9.0	7.1
Sulfation	Abs/.1mm	*ASTM D7415	>30	<b>21.6</b>	21.7	19.1

FLUID DEGRADATION		method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414	>25	<b>18.7</b>	18.9	14.6
Base Number (BN)	mg KOH/g	ASTM D2896	9.8	<b>6.9</b>	6.4	8.3




# OIL ANALYSIS REPORT


FT-IR (Direct Trend)



Base Number



Viscosity @ 100°C




VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG


FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	15.4	14.1	14.1

## GRAPHS


Ferrous Alloys




Non-ferrous Metals



Viscosity @ 100°C



Base Number



**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : SBP0007710      **Received** : 21 Jun 2024  
**Lab Number** : **06217508**      **Tested** : 24 Jun 2024  
**Unique Number** : 11090372      **Diagnosed** : 24 Jun 2024 - Wes Davis  
**Test Package** : FLEET

**SCHMIDT TRANSPORTATION - 605449**  
 108 E Bay Road  
 Plattsmouth, NE  
 US 68048  
 Contact: NICK DOTY  
 doty@liquidtrucking.com  
 T: (402)949-9398  
 F:

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)