


OIL ANALYSIS REPORT

Sample Rating Trend



Machine Id

C-142

Refrigeration Compressor

TULCO LUBSOIL SYN RL WI 100 (--- GAL)

DIAGNOSIS

Recommendation

No corrective action is recommended at this time. Resample at the next service interval to monitor.

Wear

The iron level is abnormal. All other component wear rates are normal.

Contamination

There is a moderate amount of silt (particulates < 14 microns in size) present in the oil.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

			0ct2020	Jun2024		
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		TO20000340	TO2000979	
Sample Date		Client Info		12 Jun 2024	12 Oct 2020	
Machine Age	hrs	Client Info		0	0	
Oil Age	hrs	Client Info		0	0	
Oil Changed		Client Info		N/A	N/A	
Sample Status				ABNORMAL	ABNORMAL	
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>8	<u>^</u> 22	13	
Chromium	ppm	ASTM D5185m	>2	0	0	
Nickel	ppm	ASTM D5185m		0	<1	
Titanium	ppm	ASTM D5185m		0	0	
Silver	ppm	ASTM D5185m	>2	0	<1	
Aluminum	ppm	ASTM D5185m	>3	0	0	
Lead	ppm	ASTM D5185m	>2	0	0	
Copper	ppm	ASTM D5185m	>8	0	0	
Tin	ppm	ASTM D5185m	>4	0	<1	
Antimony	ppm	ASTM D5185m			<1	
Vanadium	ppm	ASTM D5185m		0	0	
Cadmium	ppm	ASTM D5185m		0	0	
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0	2	
Barium	ppm	ASTM D5185m		0	0	
Molybdenum	ppm	ASTM D5185m		0	<1	
Manganese	ppm	ASTM D5185m		1	<1	
Magnesium	ppm	ASTM D5185m		0	<1	
Calcium	ppm	ASTM D5185m		<1	1	
Phosphorus	ppm	ASTM D5185m	1500	980	221	
Zinc	ppm	ASTM D5185m		36	<1	
Sulfur	ppm	ASTM D5185m		0	0	
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>15	2	4	
Sodium	ppm	ASTM D5185m		5	7	
Potassium	ppm	ASTM D5185m	>20	<1	0	
Water	%	ASTM D6304	>2.26	0.053	△ 0.054	
ppm Water	ppm	ASTM D6304	>22600	531	<u>▲</u> 541.4	
FLUID CLEANLIN	IESS	method	limit/base	current	history1	history2
Particles >4μm		ASTM D7647	>10000	11285	<u>194552</u>	
Particles >6µm		ASTM D7647	>2500	<u>2550</u>	△ 69662	
Particles >14μm		ASTM D7647	>320	50	<u>1034</u>	
Particles >21µm		ASTM D7647	>80	5	△ 91	
Particles >38μm		ASTM D7647	>20	0	2	
Particles >71µm		ASTM D7647	>4	0	0	
Oil Cleanliness		ISO 4406 (c)	>20/18/15	2 1/19/13	<u>\$\text{\Delta}\$ 25/23/17</u>	
FLUID DEGRADA	TION	method	limit/base	current	history1	history2

Acid Number (AN)

mg KOH/g ASTM D974 0.04

0.015

Contact/Location: TYLER FINCH - ENLCUS

Report Id: ENLCUS [WUSCAR] 06218317 (Generated: 06/26/2024 14:22:19) Rev: 1



OIL ANALYSIS REPORT





Certificate 12367

Laboratory Sample No.

: TO20000340 Lab Number : 06218317 Unique Number : 11096514

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Received : 24 Jun 2024 Tested

: 25 Jun 2024 Diagnosed : 26 Jun 2024 - Don Baldridge

Test Package : IND 2 (Additional Tests: KV100, PrtCount, VI) To discuss this sample report, contact Customer Service at 1-800-237-1369. st - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

US 74023 Contact: TYLER FINCH tyler.finch@enlink.com

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Report Id: ENLCUS [WUSCAR] 06218317 (Generated: 06/26/2024 14:22:19) Rev: 1

Contact/Location: TYLER FINCH - ENLCUS

3000 W TEXACO RD

CUSHING, OK

T: (918)399-0359