

## **OIL ANALYSIS REPORT**

Sample Rating Trend

### NORMAL

### Area **NOT** GIVEN [291541] ATLAS COPCO HOL022214 - SUNRISE FIBERGLASS

Component Compressor

#### DIAGNOSIS

#### Recommendation

Resample at the next service interval to monitor.

#### Wear

All component wear rates are normal.

#### Contamination

There is no indication of any contamination in the component.

#### Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

SAMPLE INFORM	ATION	method	limit/base	current	history1	history2
Sample Number		Client Info		UFD0002323		
Sample Date		Client Info		17 Jun 2024		
Machine Age	hrs	Client Info		34283		
Oil Age	hrs	Client Info		0		
Oil Changed	1110	Client Info		Changed		
Sample Status				NORMAL		
-			11 11 /1		11.1	
CONTAMINATION	N	method	limit/base	current	history1	history2
Water		WC Method	>0.1	NEG		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	4		
Chromium	ppm	ASTM D5185m	>5	0		
Nickel	ppm	ASTM D5185m		0		
Titanium	ppm	ASTM D5185m		0		
Silver	ppm	ASTM D5185m		0		
Aluminum	ppm	ASTM D5185m	>15	<1		
Lead	ppm	ASTM D5185m	>65	0		
Copper	ppm	ASTM D5185m	>65	9		
Tin	ppm	ASTM D5185m	>10	0		
Vanadium	ppm	ASTM D5185m		0		
Cadmium	ppm	ASTM D5185m		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	2	0		
Barium	ppm	ASTM D5185m	525	749		
Molybdenum	ppm	ASTM D5185m	10	0		
Manganese	ppm	ASTM D5185m		0		
Magnesium	ppm	ASTM D5185m	5	2		
Calcium	ppm	ASTM D5185m	10	4		
Phosphorus	ppm	ASTM D5185m	250	4		
Zinc	ppm	ASTM D5185m	100	45		
Sulfur	ppm	ASTM D5185m	400	518		
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>35	2		
Sodium	ppm	ASTM D5185m		23		
Potassium	ppm	ASTM D5185m	>20	<1		
FLUID DEGRADA		method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045		0.172		




# **OIL ANALYSIS REPORT**

VISUAL

Acid Number





					,	,
White Metal	scalar	*Visual	NONE	NONE		
Yellow Metal	scalar	*Visual	NONE	NONE		
Precipitate	scalar	*Visual	NONE	NONE		
Silt	scalar	*Visual	NONE	NONE		
Debris	scalar	*Visual	NONE	LIGHT		
Sand/Dirt	scalar	*Visual	NONE	NONE		
Appearance	scalar	*Visual	NORML	NORML		
Odor	scalar	*Visual	NORML	NORML		
Emulsified Water	scalar	*Visual	>0.1	NEG		
Free Water	scalar	*Visual		NEG		
FLUID PROPERT	IES	method				history2
Visc @ 40°C	cSt	ASTM D445	32	36.0		
SAMPLE IMAGES	5	method	limit/base	current	history1	history2
Color					no image	no image
Bottom					no image	no image
GRAPHS						
Ferrous Alloys						
<sup>10</sup> I						
8 - iron chromium						
E 6- nickel						
ā 4-						
2						
			5			
Jun 17/24			Jun17/24			
			Jur			
Non-ferrous Metals	5		Jur			
10 conner	5					
	5					
8 6 6	5					
10 8 6 4	S		uu f			
8 6 6	S		Jur			
10 8 6 4 2	5					
10 8 6 4 2	5					
10 8 10 10 10 10 10 10 10 10 10 10	5		Jur			
Viscosity @ 40°C	s		Jun17/24	Acid Number		
Viscosity @ 40°C	5		Jun17/24			
Viscosity @ 40°C	5		Jun17/24			
Viscosity @ 40°C	5		Jun17/24			
Viscosity @ 40°C	5		Jun17/24			
Viscosity @ 40°C	5		6,0.20 во 0.15 ос.00 ос.00 ос.00 ос.00 ос.00 ос.00			
Viscosity @ 40°C	5		0.00 Participant P			54
Viscosity @ 40°C	S		6,0.20 во 0.15 ос.00 ос.00 ос.00 ос.00 ос.00 ос.00			Jun17/24 +
Viscosity @ 40°C	1 Madiso Recei	ved : 24	+7/L1um +7/L1u	Jun 1724		<b>IAMICS - (MN)</b> JDICIAL ROAD
Viscosity @ 40°C	1 Madiso Recei Teste	ved : 24 d : 25	+7/L1/unr +7/L1/	βζίζιμης FL	14250 JL	<b>IAMICS - (MN)</b> JDICIAL ROAD RNSVILLE, MN
Viscosity @ 40°C	1 Madiso Recei	ved : 24 d : 25	+7/L1um +7/L1u	βζίζιμης FL	14250 JL BUF	<b>IAMICS - (MN)</b> JDICIAL ROAD

To discuss this sample report, contact Customer Service at 1-800-237-1369. \* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Laboratory

Sample No. Lab Number **Unique Number Test Package** 

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Certificate L2367

Contact/Location: Service Manager - UCFLUBUR

т:

F: