

OIL ANALYSIS REPORT

Area ELGI MSAL061064 - DOUBLE ENVELOPE Component Compressor

Recommendation

Resample at the next service interval to monitor.

Wear


All component wear rates are normal.

Contamination

There is no indication of any contamination in the component.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.



Sample Rating Trend




NORMAL

| SAMPLE INFORM | MATION | method | limit/base | current | history1 | history2 |
|------------------|---------------|-------------|------------|-------------|----------|----------|
| Sample Number | | Client Info | | UAC06218361 | | |
| Sample Date | | Client Info | | 23 Jun 2024 | | |
| Machine Age | hrs | Client Info | | 35900 | | |
| Oil Age | hrs | Client Info | | 3637 | | |
| Oil Changed | | Client Info | | Not Changd | | |
| Sample Status | | | | NORMAL | | |
| CONTAMINATION | N | method | limit/base | current | history1 | history2 |
| Water | | WC Method | >0.1 | NEG | | |
| WEAR METALS | | method | limit/base | current | history1 | history2 |
| Iron | ppm | ASTM D5185m | >50 | 0 | | |
| Chromium | ppm | ASTM D5185m | >10 | 0 | | |
| Nickel | ppm | ASTM D5185m | | 0 | | |
| Titanium | ppm | ASTM D5185m | | 0 | | |
| Silver | ppm | ASTM D5185m | | 0 | | |
| Aluminum | ppm | ASTM D5185m | >25 | 0 | | |
| Lead | ppm | ASTM D5185m | >25 | 0 | | |
| Copper | ppm | ASTM D5185m | >50 | 0 | | |
| Tin | ppm | ASTM D5185m | >15 | 0 | | |
| Vanadium | ppm | ASTM D5185m | | 0 | | |
| Cadmium | ppm | ASTM D5185m | | 0 | | |
| ADDITIVES | | method | limit/base | current | history1 | history2 |
| Boron | ppm | ASTM D5185m | | 0 | | |
| Barium | ppm | ASTM D5185m | | 0 | | |
| Molybdenum | ppm | ASTM D5185m | | 0 | | |
| Manganese | ppm | ASTM D5185m | | 0 | | |
| Magnesium | ppm | ASTM D5185m | | <1 | | |
| Calcium | ppm | ASTM D5185m | | 0 | | |
| Phosphorus | ppm | ASTM D5185m | | 1 | | |
| Zinc | ppm | ASTM D5185m | | <1 | | |
| Sulfur | ppm | ASTM D5185m | | 0 | | |
| CONTAMINANTS | | method | limit/base | current | history1 | history2 |
| Silicon | ppm | ASTM D5185m | >25 | 0 | | |
| Sodium | ppm | ASTM D5185m | | 0 | | |
| Potassium | ppm | ASTM D5185m | >20 | 0 | | |
| FLUID DEGRADA | TION | method | limit/base | current | history1 | history2 |
| Acid Number (AN) | mg KOH/g | ASTM D8045 | | 0.82 | | |



OIL ANALYSIS REPORT

VICLIAL



| VISUAL | | method | limit/base | current | history1 | history2 | |
|---|--------|-----------|------------|-------------|---|------------|--|
| White Metal | scalar | *Visual | NONE | NONE | | | |
| Yellow Metal | scalar | *Visual | NONE | NONE | | | |
| Precipitate | scalar | *Visual | NONE | NONE | | | |
| Silt | scalar | *Visual | NONE | NONE | | | |
| Debris | scalar | *Visual | NONE | NONE | | | |
| Sand/Dirt | scalar | *Visual | NONE | NONE | | | |
| Appearance | scalar | *Visual | NORML | NORML | | | |
| Odor | scalar | *Visual | NORML | NORML | | | |
| Emulsified Water | scalar | *Visual | >0.1 | NEG | | | |
| Free Water | scalar | *Visual | | NEG | | | |
| FLUID PROPERT | TIES | method | limit/base | current | history1 | history2 | |
| Visc @ 40°C | cSt | ASTM D445 | | 48.9 | | | |
| SAMPLE IMAGES | S | method | limit/base | current | history1 | history2 | |
| Color | | | | | no image | no image | |
| Bottom | | | | | no image | no image | |
| GRAPHS | | - | | | | | |
| Non-ferrous Metal | ls | | Jun23/24 | | | | |
| Viscosity @ 40°C | | | Jun23/24 | Acid Number | | | |
| 55 Abnormal | | | (B/HO) | 3 | | | |
| 45 - Abnormal 40 - Bonormal 35 - F2/62 unp | | | Jun23/24 | Jun23/24 | | Jun23/24 - | |
| WearCheck USA - 501 Madison Ave., Cary, NC 27513 JAC06218361 Received : 24 Jun 2024 J6218361 Tested : 25 Jun 2024 11096558 Diagnosed : 25 Jun 2024 - Sean Felton ND 2 Interference at 1-800-237-1369. | | | | | ATLANTIC COMPRESSORS - ACI 2144 SALEM INDUSTRIAL DRIVE SALEM, VA US 24153 Contact: BILL RIMER bill@atlanticcompressors.com | | |

To discuss this sample report, contact Customer Service at 1-800-237-1369. * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Report Id: UCATLSAL [WUSCAR] 06218361 (Generated: 06/25/2024 18:19:08) Rev: 1

Certificate L2367

Laboratory Sample No. Lab Number Unique Number Test Package

Contact/Location: BILL RIMER - UCATLSAL

T: (540)728-1147

F: (757)216-0134