

OIL ANALYSIS REPORT

SAMPLE INFORMATIO

hrs

hrs

Sample Number

Sample Date

Machine Age

Oil Changed

Sample Status

Oil Age

Area CAM **CAM (S/N FLANKING SYSTEM)**

Hydraulic System

CHEVRON HYDRAULIC AW ISO 68 (200 GAL)

DIAGNOSIS

Recommendation

We recommend you service the filters on this component. Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is a high amount of particulates present in the oil.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

	Sample	e Rating Tre	nd		
Γ					ISO
			l I allaa	.1.1	
	12014 Jan2015	Mar2016 Jul2017	Apr2018 Oct2019 May2022 S	history1	history2
	Client Info		MW0070288	MW0065416	MW0065408
	Client Info		10 Jun 2024	01 Apr 2024	24 Mar 2024
	Client Info		0	22303	0
	Client Info		0	22303	0
	Client Info			Not Changed	NI/A
	Cilent Inio		N/A	Not Ghangu	IN/A

CONTAMINATION		method	limit/base	current	history1	history2
Water		WC Method	>0.05	NEG	NEG	NEG
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>20	0	3	11
Chromium	ppm	ASTM D5185m	>10	0	0	0
Nickel	ppm	ASTM D5185m	>10	0	0	0
Titanium	ppm	ASTM D5185m		0	0	0
Silver	ppm	ASTM D5185m		0	0	0
Aluminum	ppm	ASTM D5185m	>10	0	0	0
Lead	ppm	ASTM D5185m	>20	0	0	0
Copper	ppm	ASTM D5185m	>20	5	4	4
Tin	ppm	ASTM D5185m	>10	0	0	0
Vanadium	ppm	ASTM D5185m		0	0	0
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0	0	0

Boron	ppm	ASTM D5185m	0	0		0
Barium	ppm	ASTM D5185m	0	0		0
Molybdenum	ppm	ASTM D5185m	0	0		0
Manganese	ppm	ASTM D5185m	0	0		0
Magnesium	ppm	ASTM D5185m	0	0		0
Calcium	ppm	ASTM D5185m	56	49		51
Phosphorus	ppm	ASTM D5185m	335	323	:	328
Zinc	ppm	ASTM D5185m	402	409		390
Sulfur	maa	ASTM D5185m	909	814		878

CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>15	0	0	0
Sodium	ppm	ASTM D5185m		2	<1	0
Potassium	ppm	ASTM D5185m	>20	0	0	0

FLUID CLEANLINESS	method	limit/base	current	history1	history2
Particles >4µm	ASTM D7647		99238	73147	
Particles >6µm	ASTM D7647	>1300	<u> </u>	🔺 15764	
Particles >14µm	ASTM D7647	>160	4 917	A 326	
Particles >21µm	ASTM D7647	>40	<u> </u>	36	
Particles >38µm	ASTM D7647	>10	1	1	
Particles >71µm	ASTM D7647	>3	0	0	
Oil Cleanliness	ISO 4406 (c)	>/17/14	A 24/22/17	▲ 23/21/16	
FLUID DEGRADATION	method	limit/base	current	history1	history2

Acid Number (AN)

mg KOH/g ASTM D8045

0.22 0.29 0.62

Report Id: AMESAI [WUSCAR] 06219619 (Generated: 07/02/2024 10:38:54) Rev: 1

Contact/Location: BRIAN GRIEWING - AMESAI



OIL ANALYSIS REPORT









VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	LIGHT	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	LIGHT	LIGHT	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	🔺 HEAVY
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.05	NEG	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG	NEG
FLUID PROPERT	IES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445	64.6	68.1	67.9	67.9
SAMPLE IMAGES	;	method	limit/base	current	history1	history2
Color						
Bottom						





Report Id: AMESAI [WUSCAR] 06219619 (Generated: 07/02/2024 10:38:54) Rev: 1

Contact/Location: BRIAN GRIEWING - AMESAI

Page 2 of 2