


OIL ANALYSIS REPORT

Sample Rating Trend



Machine Id

8380204 (S/N 1192)

Compressor

KAESER SIGMA (OEM) S-460 (--- LTR)

DIAGNOSIS

Recommendation

Oil and filter change at the time of sampling has been noted. No corrective action is recommended at this time. Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

Elemental level of silicon (Si) above normal indicating ingress of seal material. The amount and size of particulates present in the system are acceptable.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

			Junzuza	Junzuz4		
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		KC109402	KC106077	
Sample Date		Client Info		11 Jun 2024	15 Jun 2023	
Machine Age	hrs	Client Info		2983	1476	
Oil Age	hrs	Client Info		1507	1476	
Oil Changed		Client Info		Changed	Changed	
Sample Status				ABNORMAL	ABNORMAL	
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	0	2	
Chromium	ppm	ASTM D5185m	>10	0	0	
Nickel	ppm	ASTM D5185m	>3	0	<1	
Titanium	ppm	ASTM D5185m	>3	0	0	
Silver	ppm	ASTM D5185m	>2	0	0	
Aluminum	ppm	ASTM D5185m	>10	0	0	
Lead	ppm	ASTM D5185m	>10	0	<1	
Copper	ppm	ASTM D5185m	>50	6	9	
Tin	ppm	ASTM D5185m	>10	0	0	
Vanadium	ppm	ASTM D5185m		0	0	
Cadmium	ppm	ASTM D5185m		0	0	
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0	0	
Barium	ppm	ASTM D5185m	90	0	0	
Molybdenum	ppm	ASTM D5185m		0	0	
Manganese	ppm	ASTM D5185m		0	<1	
Magnesium	ppm	ASTM D5185m	90	27	39	
Calcium	ppm	ASTM D5185m	2	0	0	
Phosphorus	ppm	ASTM D5185m	_	0	0	
Zinc	ppm	ASTM D5185m		9	7	
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	<u> 124</u>	△ 92	
Sodium	ppm	ASTM D5185m	720	8	3	
Potassium	ppm	ASTM D5185m	>20	<1	1	
Water	%	ASTM D6304	>0.05	0.015	0.017	
ppm Water	ppm	ASTM D6304		159	179.9	
FLUID CLEANLIN		method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647		2040		
Particles >6µm		ASTM D7647	>1300	784		
Particles >14µm		ASTM D7647	>80	53		
Particles >21µm		ASTM D7647	>20	9		
Particles >38µm		ASTM D7647	>4	0		
Particles >71μm		ASTM D7647	>3	0		
Oil Cleanliness		ISO 4406 (c)	>/17/13	18/17/13		
FLUID DEGRADA	MOITA	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045	0.4	0.33	0.33	
ACIO INUITIDEI (AIN)	iliy K∪⊓/ÿ	79 LINI D0043	0.4	0.33	0.55	



OIL ANALYSIS REPORT







Certificate 12367

Laboratory Sample No. Lab Number

: KC109402 : 06219699 Unique Number : 11097896 Test Package : IND 2

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Received : 25 Jun 2024 Tested : 26 Jun 2024

Diagnosed

: 26 Jun 2024 - Don Baldridge Contact: Service Manager

To discuss this sample report, contact Customer Service at 1-800-237-1369.

 st - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Report Id: INTALLPA [WUSCAR] 06219699 (Generated: 06/28/2024 00:17:37) Rev: 1

Contact/Location: Service Manager - INTALLPA

802 E FAIRMONT ST

ALLENTOWN, PA

US 18106

T:

F: