

OIL ANALYSIS REPORT

Sample Rating Trend

WATER

Area S-460 Machine to KAESER 1097 - BELLE TIRE

Component Compressor

DIAGNOSIS

Recommendation

Oil and filter change at the time of sampling has been noted. We recommend an early resample to monitor this condition.

Wear

All component wear rates are normal.

Contamination

Moderate concentration of visible dirt/debris present in the oil. There is a light concentration of water present in the oil. Excessive free water present.


Fluid Condition

The AN level is acceptable for this fluid.

SAMPLE INFORM	IATION	method	limit/base	current	history1	history2
Sample Number		Client Info		UDI0000383		
Sample Date		Client Info		19 Jun 2024		
Machine Age	hrs	Client Info		128		
Oil Age	hrs	Client Info		128		
Oil Changed		Client Info		Changed		
Sample Status				ATTENTION		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	38		
Chromium	ppm	ASTM D5185m	>10	0		
Nickel	ppm	ASTM D5185m	>3	<1		
Titanium	ppm	ASTM D5185m	>3	0		
Silver	ppm	ASTM D5185m	>2	0		
Aluminum	ppm	ASTM D5185m	>10	1		
Lead	ppm	ASTM D5185m	>10	0		
Copper	ppm	ASTM D5185m	>50	4		
Tin	ppm	ASTM D5185m	>10	0		
Vanadium	ppm	ASTM D5185m		0		
Cadmium	ppm	ASTM D5185m		0		
ADDITIVES		method	limit/base	current	history1	history2
ADDITIVES Boron	ppm	method ASTM D5185m	limit/base	current 0	history1	history2
	ppm ppm		limit/base 90			
Boron		ASTM D5185m		0		
Boron Barium	ppm	ASTM D5185m ASTM D5185m		0 8		
Boron Barium Molybdenum	ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m		0 8 0		
Boron Barium Molybdenum Manganese	ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	90 90	0 8 0 <1		
Boron Barium Molybdenum Manganese Magnesium	ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	90 90	0 8 0 <1 5		
Boron Barium Molybdenum Manganese Magnesium Calcium	ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	90 90	0 8 0 <1 5 0	 	
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus	ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	90 90	0 8 0 <1 5 0 0	 	
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc	ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	90 90	0 8 0 <1 5 0 0 0 64	 	
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur	ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	90 90 2	0 8 0 <1 5 0 0 0 64 22832		
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINANTS	ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	90 90 2 limit/base	0 8 0 <1 5 0 0 0 64 22832 current	 history1	 history2
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINANTS Silicon	ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m method ASTM D5185m	90 90 2 limit/base	0 8 0 <1 5 0 0 0 64 22832 current <1	 history1	 history2
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINANTS Silicon Sodium	ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m method ASTM D5185m	90 90 2 limit/base >25	0 8 0 <1 5 0 0 0 64 22832 current <1 2	 history1	 history2
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINANTS Silicon Sodium Potassium	ppm ppm ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m	90 90 2 <u>limit/base</u> >25 >20	0 8 0 <1 5 0 0 0 64 22832 current <1 2 2	 history1	 history2
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINANTS Silicon Sodium Potassium Water	ppm ppm ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m	90 2 2 <u>limit/base</u> >25 >20 >20 >0.05	0 8 0 <1 5 0 0 0 64 22832 current <1 2 2 2 0.089	 history1 	 history2



OIL ANALYSIS REPORT







VISUAL		method	limit/base	current	history1	history
White Metal	scalar	*Visual	NONE	NONE		
Yellow Metal	scalar	*Visual	NONE	NONE		
Precipitate	scalar	*Visual	NONE	NONE		
Silt	scalar	*Visual	NONE	NONE		
Debris	scalar	*Visual	NONE	MODER		
Sand/Dirt	scalar	*Visual	NONE	NONE		
Appearance	scalar	*Visual	NORML	NORML		
Odor	scalar	*Visual	NORML	NORML		
Emulsified Water	scalar	*Visual	>0.05	— 0.2%		
Free Water	scalar	*Visual		<mark> </mark> >10%		
FLUID PROPERT	IES	method	limit/base	current	history1	history
Visc @ 40°C	cSt	ASTM D445	46	43.5		
SAMPLE IMAGES	6	method	limit/base	current	history1	history
Color					no image	no image
Bottom					no image	no image
Non-ferrous Metals	S		Jun 19/24			
Viscosity @ 40°C			- 10/24	Acid Number		
50 - Abnormal			(B) 0.5 (B) 0.4 (B) 0.4 (B) 0.3 (B) 0.3 (C) 0.4 (C) 0.5 (C) 0.4 (C) 0.5 (C) 0.	0 - Base		
Co 0 + 45 + Base 3 Abnormal			Ë0.3	0		
			- 0.2	0		
35			F 0.1	0+		
dun 19/24				Jun19/24		
: WearCheck USA - 50			, NC 27513		NDUSTRIES - DO	
: UDI0000383 r : 06219822 r : 11098019 e : IND 2 (Additional Tes rt. contact Customer Servi	ts: KF)	ed : 26 nosed : 27	5 Jun 2024 5 Jun 2024 Jun 2024 - Dor	n Baldridge		RTISS STRI RS GROVE US 60 HAEL FER

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012) F: (630)960-3931

Report Id: UCDELDOW [WUSCAR] 06219822 (Generated: 06/30/2024 16:40:43) Rev: 1

Certificate L2367

Contact/Location: MICHAEL FERRIS - UCDELDOW

T: