

OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL



Machine Id

INGERSOLL RAND CBV195755 - CINTAS GREENVILLE

Compressor

INGERSOLL-RAND SSR ULTRA COOLANT (3 GAL)

| D | IA | Gľ | VО | SI | S | |
|---|----|----|----|----|---|--|
| | | | | | | |

Recommendation

Resample at the next service interval to monitor.

All component wear rates are normal.

Contamination

There is no indication of any contamination in the


Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

| (3 GAL) | | Augzuro Juiz | JIB Janzuzz Wayzuzz Sepz | 022 Nov2022 Mar2023 Sep2023 Deci | 1023 JUNZ024 | |
|------------------|----------|--------------|--------------------------|----------------------------------|--------------|-------------|
| SAMPLE INFORM | MATION | method | limit/base | current | history1 | history2 |
| Sample Number | | Client Info | | WC0915325 | WC0863653 | WC0845189 |
| Sample Date | | Client Info | | 20 Jun 2024 | 27 Dec 2023 | 11 Sep 2023 |
| Machine Age | hrs | Client Info | | 5427 | 2712 | 1084 |
| Oil Age | hrs | Client Info | | 0 | 0 | 1000 |
| Oil Changed | | Client Info | | Not Changd | Not Changd | N/A |
| Sample Status | | | | NORMAL | ABNORMAL | NORMAL |
| CONTAMINATIO | N | method | limit/base | current | history1 | history2 |
| Water | | WC Method | >0.1 | NEG | NEG | NEG |
| WEAR METALS | | method | limit/base | current | history1 | history2 |
| Iron | ppm | ASTM D5185m | >50 | 0 | 0 | 0 |
| Chromium | ppm | ASTM D5185m | >10 | 0 | <1 | 0 |
| Nickel | ppm | ASTM D5185m | | <1 | 0 | 0 |
| Titanium | ppm | ASTM D5185m | | 0 | 0 | <1 |
| Silver | ppm | ASTM D5185m | | 0 | 0 | 0 |
| Aluminum | ppm | ASTM D5185m | >25 | <1 | 1 | 2 |
| Lead | ppm | ASTM D5185m | >25 | 0 | 0 | 0 |
| Copper | ppm | ASTM D5185m | >50 | <1 | 0 | <1 |
| Tin | ppm | ASTM D5185m | >15 | 0 | 0 | <1 |
| Vanadium | ppm | ASTM D5185m | | 0 | 0 | 0 |
| Cadmium | ppm | ASTM D5185m | | 0 | 0 | 0 |
| ADDITIVES | | method | limit/base | current | history1 | history2 |
| Boron | ppm | ASTM D5185m | 0 | 0 | 0 | 0 |
| Barium | ppm | ASTM D5185m | 500 | 9 | 0 | 0 |
| Molybdenum | ppm | ASTM D5185m | 0 | 0 | 0 | 0 |
| Manganese | ppm | ASTM D5185m | | <1 | 0 | 0 |
| Magnesium | ppm | ASTM D5185m | 0 | 0 | <1 | 0 |
| Calcium | ppm | ASTM D5185m | 0 | 0 | <1 | 0 |
| Phosphorus | ppm | ASTM D5185m | 20 | 494 | 114 | 97 |
| Zinc | ppm | ASTM D5185m | 0 | 8 | 63 | 75 |
| Sulfur | ppm | ASTM D5185m | 200 | 96 | 0 | 89 |
| CONTAMINANTS | 3 | method | limit/base | current | history1 | history2 |
| Silicon | ppm | ASTM D5185m | >25 | 0 | <1 | <1 |
| Sodium | ppm | ASTM D5185m | | 5 | 8 | 3 |
| Potassium | ppm | ASTM D5185m | >20 | 1 | <1 | 0 |
| FLUID DEGRADA | NOITA | method | limit/base | current | history1 | history2 |
| Acid Number (AN) | mg KOH/g | ASTM D8045 | | 0.09 | 0.19 | 0.16 |




OIL ANALYSIS REPORT





| VISUAL | | method | limit/base | current | history1 | history2 |
|-------------------------|--------|-----------|------------|---------|--------------|----------|
| White Metal | scalar | *Visual | NONE | NONE | NONE | NONE |
| Yellow Metal | scalar | *Visual | NONE | NONE | NONE | NONE |
| Precipitate | scalar | *Visual | NONE | NONE | NONE | NONE |
| Silt | scalar | *Visual | NONE | NONE | ▲ MODER | NONE |
| Debris | scalar | *Visual | NONE | NONE | NONE | NONE |
| Sand/Dirt | scalar | *Visual | NONE | NONE | NONE | NONE |
| Appearance | scalar | *Visual | NORML | NORML | NORML | NORML |
| Odor | scalar | *Visual | NORML | NORML | NORML | NORML |
| Emulsified Water | scalar | *Visual | >0.1 | NEG | 0.2% | NEG |
| Free Water | scalar | *Visual | | NEG | <u>▲</u> 1.0 | NEG |
| FLUID PROPERT | TES | method | limit/base | current | history1 | history2 |
| Visc @ 40°C | cSt | ASTM D445 | 49.4 | 47.6 | 44.8 | 44.1 |
| SAMPLE IMAGES | 6 | method | limit/base | current | history1 | history2 |
| | | | | | W. 101 | W. D.A. |


Color


Bottom















Certificate 12367

Laboratory Sample No.

Test Package : IND 2

: WC0915325 Lab Number : 06219843 Unique Number : 11098040

To discuss this sample report, contact Customer Service at 1-800-237-1369.

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Received : 25 Jun 2024 **Tested** Diagnosed

: 26 Jun 2024 : 27 Jun 2024 - Don Baldridge

ELEVATED INDUSTRIAL SOLUTIONS - EIS 302 HUGHES ST FOUNTAIN INN, SC US 29644 Contact: DARRIN WARD

dward@elevatedindustrial.com

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

F: (864)862-7653

T: