




# OIL ANALYSIS REPORT

Sample Rating Trend



**NORMAL**



Machine Id

**MAIN**

Component

**Diesel Engine**

Fluid

**DIESEL ENGINE OIL SAE 15W40 (--- GAL)**

## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor. Please specify the component make and model with your next sample.

### Wear

Metal levels are typical for a new component breaking in.

### Contamination

There is no indication of any contamination in the oil.

### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION		method	limit/base	current	history1	history2
Sample Number	Client Info			<b>WC0827469</b>	WC0568417	---
Sample Date	Client Info			<b>04 Jun 2024</b>	01 Apr 2021	---
Machine Age	hrs	Client Info		<b>360</b>	243	---
Oil Age	hrs	Client Info		<b>0</b>	0	---
Oil Changed	Client Info			<b>Changed</b>	Changed	---
Sample Status				<b>NORMAL</b>	NORMAL	---

CONTAMINATION		method	limit/base	current	history1	history2
Fuel	WC Method	>5		<b>&lt;1.0</b>	<1.0	---
Water	WC Method	>0.2		<b>NEG</b>	NEG	---
Glycol	WC Method			<b>NEG</b>	NEG	---

WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>100	<b>1</b>	29	---
Chromium	ppm	ASTM D5185m	>20	<b>0</b>	2	---
Nickel	ppm	ASTM D5185m	>4	<b>0</b>	<1	---
Titanium	ppm	ASTM D5185m		<b>0</b>	<1	---
Silver	ppm	ASTM D5185m	>3	<b>0</b>	0	---
Aluminum	ppm	ASTM D5185m	>20	<b>2</b>	3	---
Lead	ppm	ASTM D5185m	>40	<b>&lt;1</b>	4	---
Copper	ppm	ASTM D5185m	>330	<b>2</b>	8	---
Tin	ppm	ASTM D5185m	>15	<b>0</b>	1	---
Antimony	ppm	ASTM D5185m		<b>---</b>	0	---
Vanadium	ppm	ASTM D5185m		<b>0</b>	<1	---
Cadmium	ppm	ASTM D5185m		<b>0</b>	0	---

ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	250	<b>64</b>	309	---
Barium	ppm	ASTM D5185m	10	<b>0</b>	0	---
Molybdenum	ppm	ASTM D5185m	100	<b>15</b>	116	---
Manganese	ppm	ASTM D5185m		<b>&lt;1</b>	1	---
Magnesium	ppm	ASTM D5185m	450	<b>95</b>	638	---
Calcium	ppm	ASTM D5185m	3000	<b>2177</b>	1547	---
Phosphorus	ppm	ASTM D5185m	1150	<b>921</b>	777	---
Zinc	ppm	ASTM D5185m	1350	<b>1077</b>	930	---
Sulfur	ppm	ASTM D5185m	4250	<b>4155</b>	2408	---




CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	<b>6</b>	8	---
Sodium	ppm	ASTM D5185m	>158	<b>1</b>	3	---
Potassium	ppm	ASTM D5185m	>20	<b>4</b>	2	---

INFRA-RED		method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844	>3	<b>0.1</b>	0.4	---
Nitration	Abs/cm	*ASTM D7624	>20	<b>5.3</b>	7	---
Sulfation	Abs/.1mm	*ASTM D7415	>30	<b>15.8</b>	22.4	---

FLUID DEGRADATION		method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414	>25	<b>9.8</b>	16.7	---
Base Number (BN)	mg KOH/g	ASTM D2896	8.5	<b>7.6</b>	---	---











# OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	---
Yellow Metal	scalar	*Visual	NONE	NONE	---
Precipitate	scalar	*Visual	NONE	NONE	---
Silt	scalar	*Visual	NONE	NONE	---
Debris	scalar	*Visual	NONE	NONE	---
Sand/Dirt	scalar	*Visual	NONE	NONE	---
Appearance	scalar	*Visual	NORML	NORML	---
Odor	scalar	*Visual	NORML	NORML	---
Emulsified Water	scalar	*Visual	>0.2	NEG	---
Free Water	scalar	*Visual		NEG	---

FLUID PROPERTIES	method	limit/base	current	history1	history2	
Visc @ 100°C	cSt	ASTM D445	14.4	<b>13.5</b>	13.4	---

### GRAPHS



**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : WC0827469      **Received** : 25 Jun 2024  
**Lab Number** : **06220574**      **Tested** : 27 Jun 2024  
**Unique Number** : 11098771      **Diagnosed** : 27 Jun 2024 - Wes Davis  
**Test Package** : MOB 1 ( Additional Tests: TBN )

**PARKWAY CLINICAL LABS**  
 3494 PROGRESS DR  
 BENSLEM, PA  
 US 19020  
 Contact: DENISE  
 dservis@parkwayclinical.com  
 T: (215)245-1425  
 F:

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)