




# OIL ANALYSIS REPORT

Area  
**{UNASSIGNED}**  
 Machine Id  
**CATERPILLAR 91537**  
 Component  
**Diesel Engine**  
 Fluid  
**AMERIGUARD 10W30 (8 QTS)**

## Sample Rating Trend



**NORMAL**



### DIAGNOSIS

#### Recommendation

Resample at the next service interval to monitor.

#### Wear

All component wear rates are normal.

#### Contamination

There is no indication of any contamination in the oil.

#### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

### SAMPLE INFORMATION

|               | method      | limit/base  | current            | history1 | history2 |
|---------------|-------------|-------------|--------------------|----------|----------|
| Sample Number | Client Info |             | <b>SBP0007471</b>  | ---      | ---      |
| Sample Date   | Client Info |             | <b>18 Jun 2024</b> | ---      | ---      |
| Machine Age   | hrs         | Client Info | <b>3146</b>        | ---      | ---      |
| Oil Age       | hrs         | Client Info | <b>253</b>         | ---      | ---      |
| Oil Changed   | Client Info |             | <b>Changed</b>     | ---      | ---      |
| Sample Status |             |             | <b>NORMAL</b>      | ---      | ---      |

### CONTAMINATION

|        | method    | limit/base | current        | history1 | history2 |
|--------|-----------|------------|----------------|----------|----------|
| Fuel   | WC Method | >5         | <b>&lt;1.0</b> | ---      | ---      |
| Water  | WC Method | >0.2       | <b>NEG</b>     | ---      | ---      |
| Glycol | WC Method |            | <b>NEG</b>     | ---      | ---      |

### WEAR METALS

|          | method | limit/base       | current      | history1 | history2 |
|----------|--------|------------------|--------------|----------|----------|
| Iron     | ppm    | ASTM D5185m >100 | <b>30</b>    | ---      | ---      |
| Chromium | ppm    | ASTM D5185m >20  | <b>&lt;1</b> | ---      | ---      |
| Nickel   | ppm    | ASTM D5185m >2   | <b>0</b>     | ---      | ---      |
| Titanium | ppm    | ASTM D5185m >2   | <b>0</b>     | ---      | ---      |
| Silver   | ppm    | ASTM D5185m >2   | <b>0</b>     | ---      | ---      |
| Aluminum | ppm    | ASTM D5185m >25  | <b>8</b>     | ---      | ---      |
| Lead     | ppm    | ASTM D5185m >40  | <b>0</b>     | ---      | ---      |
| Copper   | ppm    | ASTM D5185m >330 | <b>2</b>     | ---      | ---      |
| Tin      | ppm    | ASTM D5185m >15  | <b>0</b>     | ---      | ---      |
| Vanadium | ppm    | ASTM D5185m      | <b>0</b>     | ---      | ---      |
| Cadmium  | ppm    | ASTM D5185m      | <b>0</b>     | ---      | ---      |

### ADDITIVES

|            | method | limit/base  | current     | history1 | history2 |
|------------|--------|-------------|-------------|----------|----------|
| Boron      | ppm    | ASTM D5185m | <b>4</b>    | ---      | ---      |
| Barium     | ppm    | ASTM D5185m | <b>0</b>    | ---      | ---      |
| Molybdenum | ppm    | ASTM D5185m | <b>58</b>   | ---      | ---      |
| Manganese  | ppm    | ASTM D5185m | <b>0</b>    | ---      | ---      |
| Magnesium  | ppm    | ASTM D5185m | <b>934</b>  | ---      | ---      |
| Calcium    | ppm    | ASTM D5185m | <b>1110</b> | ---      | ---      |
| Phosphorus | ppm    | ASTM D5185m | <b>963</b>  | ---      | ---      |
| Zinc       | ppm    | ASTM D5185m | <b>1324</b> | ---      | ---      |
| Sulfur     | ppm    | ASTM D5185m | <b>3170</b> | ---      | ---      |

### CONTAMINANTS

|           | method | limit/base      | current  | history1 | history2 |
|-----------|--------|-----------------|----------|----------|----------|
| Silicon   | ppm    | ASTM D5185m >25 | <b>6</b> | ---      | ---      |
| Sodium    | ppm    | ASTM D5185m     | <b>1</b> | ---      | ---      |
| Potassium | ppm    | ASTM D5185m >20 | <b>2</b> | ---      | ---      |

### INFRA-RED




|           | method   | limit/base      | current     | history1 | history2 |
|-----------|----------|-----------------|-------------|----------|----------|
| Soot %    | %        | *ASTM D7844 >3  | <b>0.2</b>  | ---      | ---      |
| Nitration | Abs/cm   | *ASTM D7624 >20 | <b>7.6</b>  | ---      | ---      |
| Sulfation | Abs/.1mm | *ASTM D7415 >30 | <b>18.1</b> | ---      | ---      |

### FLUID DEGRADATION

|                  | method   | limit/base      | current     | history1 | history2 |
|------------------|----------|-----------------|-------------|----------|----------|
| Oxidation        | Abs/.1mm | *ASTM D7414 >25 | <b>14.2</b> | ---      | ---      |
| Base Number (BN) | mg KOH/g | ASTM D2896      | <b>9.4</b>  | ---      | ---      |







# OIL ANALYSIS REPORT



| VISUAL           | method | limit/base | current | history1     | history2 |
|------------------|--------|------------|---------|--------------|----------|
| White Metal      | scalar | *Visual    | NONE    | <b>NONE</b>  | ---      |
| Yellow Metal     | scalar | *Visual    | NONE    | <b>NONE</b>  | ---      |
| Precipitate      | scalar | *Visual    | NONE    | <b>NONE</b>  | ---      |
| Silt             | scalar | *Visual    | NONE    | <b>NONE</b>  | ---      |
| Debris           | scalar | *Visual    | NONE    | <b>NONE</b>  | ---      |
| Sand/Dirt        | scalar | *Visual    | NONE    | <b>NONE</b>  | ---      |
| Appearance       | scalar | *Visual    | NORML   | <b>NORML</b> | ---      |
| Odor             | scalar | *Visual    | NORML   | <b>NORML</b> | ---      |
| Emulsified Water | scalar | *Visual    | >0.2    | <b>NEG</b>   | ---      |
| Free Water       | scalar | *Visual    |         | <b>NEG</b>   | ---      |

| FLUID PROPERTIES | method | limit/base | current     | history1 | history2 |
|------------------|--------|------------|-------------|----------|----------|
| Visc @ 100°C     | cSt    | ASTM D445  | <b>10.7</b> | ---      | ---      |

## GRAPHS



**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : SBP0007471      **Received** : 26 Jun 2024  
**Lab Number** : **06221027**      **Tested** : 27 Jun 2024  
**Unique Number** : 11099224      **Diagnosed** : 27 Jun 2024 - Wes Davis  
**Test Package** : FLEET

**GAGE COUNTY HIGHWAY DEPARTMENT**  
 823 SOUTH 8TH ST  
 BEATRICE, NE  
 US 68310  
 Contact: MARK KUHNKE  
 mkuhnke@gagecountyne.gov  
 T: (402)223-1395  
 F: (402)223-1351

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)