


OIL ANALYSIS REPORT

Sample Rating Trend



Machine Id

LEROI 112718 (S/N 5680X73)

Compressor

CIMARRON HB-150 (--- GAL)

DIAGNOSIS

Recommendation

We advise that you follow the water drain-off procedure for this component. We recommend you service the filters on this component. We recommend an early resample to monitor this condition.

Wear

All component wear rates are normal.

Contamination

There is a high amount of particulates present in the oil. There is a high concentration of water present in the oil.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

			Apr2024	Jun2024		
SAMPLE INFORM	MATION	method	limit/base	ourront.	hiotonut	hiotony
	MATION		iimiybase	current	history1	history2
Sample Number		Client Info		TO90004548	TO90004036	
Sample Date		Client Info		12 Jun 2024	04 Apr 2024	
Machine Age	hrs	Client Info		0	0	
Oil Age	hrs	Client Info		0	0	
Oil Changed		Client Info		N/A	Not Changd	
Sample Status				ABNORMAL	ABNORMAL	
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	0	<1	
Chromium	ppm	ASTM D5185m	>10	<1	0	
Nickel	ppm	ASTM D5185m		0	0	
Titanium	ppm	ASTM D5185m		0	0	
Silver	ppm	ASTM D5185m		0	0	
Aluminum	ppm	ASTM D5185m	>25	2	2	
Lead	ppm	ASTM D5185m	>25	0	0	
Copper	ppm	ASTM D5185m	>50	0	<1	
Tin	ppm	ASTM D5185m	>15	0	<1	
Vanadium	ppm	ASTM D5185m		0	<1	
Cadmium	ppm	ASTM D5185m		0	0	
ADDITIVES	1-1-	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	0	1	0	
Barium	ppm	ASTM D5185m	0	0	0	
Molybdenum	ppm	ASTM D5185m	0	0	0	
Manganese	ppm	ASTM D5185m		0	0	
Magnesium	ppm	ASTM D5185m	0	<1	<1	
Calcium	ppm	ASTM D5185m	0	0	5	
Phosphorus	ppm	ASTM D5185m	0	0	54	
Zinc	ppm	ASTM D5185m	0	0	14	
Sulfur	ppm	ASTM D5185m	0	37	528	
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	0	0	
Sodium	ppm	ASTM D5185m		4	6	
Potassium	ppm	ASTM D5185m	>20	1	2	
Water	%	ASTM D6304	>2.26	1.97	1.691	
ppm Water	ppm	ASTM D6304	>22600	19700	△ 16912	
FLUID CLEANLIN	IESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>10000	20325	<u>^</u> 21906	
Particles >6µm		ASTM D7647	>2500	A 7857	<u>▲</u> 6061	
Particles >14μm		ASTM D7647	>320	▲ 383	△ 530	
Particles >21µm		ASTM D7647	>80	57	67	
Particles >38μm		ASTM D7647	>20	1	0	
Particles >71μm		ASTM D7647	>4	0	0	
Oil Cleanliness		ISO 4406 (c)	>20/18/15	22/20/16	<u>22/20/16</u>	
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045		0.24	0.37	



OIL ANALYSIS REPORT







Certificate 12367

Laboratory Sample No.

Lab Number : 06221307 Unique Number : 11099504

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 : TO90004548

Received : 26 Jun 2024 **Tested** : 27 Jun 2024 Diagnosed

: 28 Jun 2024 - Don Baldridge

Test Package : IND 2 (Additional Tests: KF, KV100, PrtCount, VI)

4425 GRANDI RD, UNIT F CARLSBAD, NM UM 88220-8923 Contact: CARLOS LEAL cleal@cimarron.com

T:

F:

Page 2 of 2

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

To discuss this sample report, contact Customer Service at 1-800-237-1369.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Contact/Location: CARLOS LEAL - CIMCAR