

OIL ANALYSIS REPORT

Area LACTOSE Machine Id CY03AG01GB01 Component

Component Gearbox Fluid MOBIL SHC CIBUS 220 (5 QTS)

DIAGNOSIS

A Recommendation

No corrective action is recommended at this time. Resample at the next service interval to monitor.

Wear


All component wear rates are normal.

Contamination

Moderate concentration of visible dirt/debris present in the oil.

Fluid Condition

The condition of the oil is acceptable for the time in service.




SAMPLE INFORM	IATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0936607	WC0884889	WC0805938
Sample Date		Client Info		30 Jun 2024	31 Dec 2023	02 Jul 2023
Machine Age	mths	Client Info		0	0	0
Oil Age	mths	Client Info		0	0	0
Oil Changed		Client Info		N/A	N/A	N/A
Sample Status				ABNORMAL	NORMAL	NORMAL
CONTAMINATION		method	limit/base	current	history1	history2
Water	•	WC Method		NEG	NEG	NEG
WEAR METALS		method	limit/base	-	history1	history2
Iron	ppm	ASTM D5185m	>200	<1	1	<1
Chromium	ppm	ASTM D5185m		<1	<1	0
Nickel	ppm	ASTM D5185m	>15	0	<1	<1
Titanium	ppm	ASTM D5185m		<1	0	0
Silver	ppm	ASTM D5185m		0	0	0
Aluminum	ppm	ASTM D5185m	>25	2	2	<1
Lead	ppm	ASTM D5185m	>100	0	<1	0
Copper	ppm	ASTM D5185m		<1	<1	0
Tin	ppm		>25	0	<1	0
Vanadium		ASTM D5185m	225	0	0	0
Cadmium	ppm	ASTM D5185m		0	<1	0
	ppm					-
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0	0	0
Barium	ppm	ASTM D5185m		0	2	0
Molybdenum	ppm	ASTM D5185m		0	<1	0
Manganese	ppm	ASTM D5185m		0	0	<1
Magnesium	ppm	ASTM D5185m		<1	0	0
Calcium	ppm	ASTM D5185m		0	0	0
Phosphorus	ppm	ASTM D5185m		978	1166	672
Zinc	ppm	ASTM D5185m		11	7	1
Sulfur	ppm	ASTM D5185m		36	12	52
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>50	25	36	21
Sodium	ppm	ASTM D5185m		0	0	<1
Potassium	ppm	ASTM D5185m	>20	<1	2	2
VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE		NONE	NONE
Beenie						
	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar scalar	*Visual *Visual	NONE NORML	NONE NORML	NONE	NORML
Sand/Dirt Appearance Odor						
Sand/Dirt Appearance	scalar	*Visual	NORML	NORML	NORML	NORML

Submitted By: MICHAEL VILLASENOR



OIL ANALYSIS REPORT



	FLUID PROPERTIE	ES I	nethod	limit/base	current	history1	history2
	Visc @ 40°C	cSt AS	STM D445	222	222	230	237
•	SAMPLE IMAGES	I	method	limit/base	current	history1	history2
	Color				no image	no image	no image
	Bottom				no image	no image	no image
	GRAPHS						
1	Ferrous Alloys						
uudd 1	9 - copper 8 - lead 7	Jul322 Dec28/22	Jul2/23	Jun30/24			
250 Ab	El/Bin El/Bin Viscosity @ 40°C Abnormal	Jul3/22	Jul2/23	Jun30/24			
24 23 (J-0(t) 22 20 (J-0(t) 23 20 20 19 18	0 - Base 0 - Abnormal 0 - Abnormal	F					
	U + + + + + + + + 270 mp + + €1/020mp VearCheck USA - 501 M VC0936607	ă	we., Cary	, NC 27513 Jul 2024		LEPRINO FOC	DS-GREELE
ber :0	6234133 1122967	Tested	: 12	Jul 2024 2 Jul 2024	Poldridae		GREELEY, C



Lab Number : 06234133 estea Diagnosed Unique Number : 11122967 : 14 Jul 2024 - Don Baldridge Test Package : IND 1 Contact: ERIC KLINE Certificate L2367 To discuss this sample report, contact Customer Service at 1-800-237-1369. EKLINE@LEPRINOFOODS.COM * - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Report Id: LEPGRE [WUSCAR] 06234133 (Generated: 07/14/2024 11:22:09) Rev: 2

Submitted By: MICHAEL VILLASENOR

Page 2 of 2

T:

US 80631-5909

F: (970)347-5190