

OIL ANALYSIS REPORT

Sample Rating Trend NORMAL



Machine Id ATLAS COPCO AC-122-1 - B67178 (S/N APF237854)

North Compressor

Fluid ATLAS COPCO ROTO Z FLUID (--- GAL)

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

The amount and size of particulates present in the system are acceptable. There is no indication of any contamination in the oil.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.


SAMPLE INFORM	IATION	method	limit/base	current	history1	history2	
Sample Number		Client Info		WC0953085	WC0865323	WC0808585	
Sample Date		Client Info		08 Jul 2024	23 Jan 2024	30 Oct 2023	
Machine Age	hrs	Client Info		17694	15760	16990	
Oil Age	hrs	Client Info		0	0	0	
Oil Changed		Client Info		Changed	Not Changd	Changed	
Sample Status				NORMAL	NORMAL	NORMAL	
CONTAMINATIO	N	method	limit/base	current	history1	history2	
Water		WC Method	>0.1	NEG	NEG	NEG	
WEAR METALS		method	limit/base	current	history1	history2	
Iron	ppm	ASTM D5185m	>50	0	0	0	
Chromium	ppm	ASTM D5185m	>5	0	0	0	
Nickel	ppm	ASTM D5185m		0	0	0	
Titanium	ppm	ASTM D5185m		0	0	0	
Silver	ppm	ASTM D5185m		0	0	0	
Aluminum	ppm	ASTM D5185m	>15	0	0	0	
Lead	ppm	ASTM D5185m	>65	0	0	0	
Copper	ppm	ASTM D5185m		0	0	0	
Tin	ppm	ASTM D5185m	>10	0	0	0	
Vanadium	ppm	ASTM D5185m	210	0	0	0	
Cadmium	ppm	ASTM D5185m		0	0	0	
	ppm			-	-	-	
ADDITIVES		method	limit/base	current	history1	history2	
Boron	ppm	ASTM D5185m		0	0	0	
Barium	ppm	ASTM D5185m		0	0	0	
Molybdenum	ppm	ASTM D5185m		0	0	0	
Manganese	ppm	ASTM D5185m		0	0	0	
Magnesium	ppm	ASTM D5185m		0	0	0	
Calcium	ppm	ASTM D5185m		3	0	0	
Phosphorus	ppm	ASTM D5185m		461	452	452	
Zinc	ppm	ASTM D5185m		0	0	0	
Sulfur	ppm	ASTM D5185m		686	628	585	
CONTAMINANTS	;	method	limit/base	current	history1	history2	
Silicon	ppm	ASTM D5185m	>35	<1	0	0	
Sodium	ppm	ASTM D5185m		2	<1	<1	
Potassium	ppm	ASTM D5185m	>20	0	0	0	
FLUID CLEANLIN	IESS	method	limit/base	current	history1	history2	
Particles >4µm		ASTM D7647	>10000	238	2873	332	
Particles >6µm		ASTM D7647	>2500	101	292	91	
Particles >14µm		ASTM D7647	>320	19	9	11	
Particles >21µm		ASTM D7647	>80	5	2	3	
Particles >38µm		ASTM D7647	>20	0	0	1	
Particles >71µm		ASTM D7647	>4	0	0	0	
Oil Cleanliness		ISO 4406 (c)	>20/18/15	15/14/11	19/15/10	16/14/11	
FLUID DEGRADA		method	limit/base	current	history1	history2	
Acid Number (AN)	mg KOH/g	ASTM D8045		0.26	0.27	0.25	
2:34:22) Rev: 1		Contact/Location: JOSEPH RUSSELL - BURNEV					


Report Id: BURNEV [WUSCAR] 06234818 (Generated: 07/15/2024 12:34:22) Rev: 1


Contact/Location: JOSEPH RUSSELL - BURNEV




OIL ANALYSIS REPORT











VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.1	NEG	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG	NEG
FLUID PROPERTIES		method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445		65.9	67.1	66.0
SAMPLE IMAGES		method	limit/base	current	history1	history2
Color						





Report Id: BURNEV [WUSCAR] 06234818 (Generated: 07/15/2024 12:34:22) Rev: 1

Contact/Location: JOSEPH RUSSELL - BURNEV

Page 2 of 2