

### **OIL ANALYSIS REPORT**

Sample Rating Trend



Machine Id

# ROLL STAND 4415 (S/N 04415)

Component Hydraulic System AW HYDRAULIC OIL ISO 46 (--- GAL)

#### DIAGNOSIS

#### Recommendation

Resample at the next service interval to monitor. The fluid was not specified, however, a fluid match indicates that this fluid is (GENERIC) AW HYDRAULIC OIL ISO 46. Please confirm. Please specify the component make and model with your next sample.

#### Wear

All component wear rates are normal.

#### Contamination

The system cleanliness is acceptable for your target ISO 4406 cleanliness code. The system and fluid cleanliness is acceptable.

#### Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.


SAMPLE INFORM	1ATION	method	limit/base	current	history1	history2
Sample Number		Client Info		PTK0005321		
Sample Date		Client Info		18 Jun 2024		
Machine Age	hrs	Client Info		0		
Oil Age	hrs	Client Info		0		
Oil Changed		Client Info		N/A		
Sample Status				NORMAL		
CONTAMINATION	١	method	limit/base	current	history1	history2
Water		WC Method	>0.1	NEG		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>20	<1		
Chromium	ppm	ASTM D5185m	>10	2		
Nickel	ppm	ASTM D5185m	>10	0		
Titanium	ppm	ASTM D5185m		0		
Silver	ppm	ASTM D5185m		0		
Aluminum	ppm	ASTM D5185m	>10	0		
Lead	ppm	ASTM D5185m	>10	0		
Copper	ppm	ASTM D5185m	>75	2		
Tin	ppm	ASTM D5185m	>10	0		
Vanadium	ppm	ASTM D5185m		0		
Cadmium	ppm	ASTM D5185m		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	5	0		
Barium	ppm	ASTM D5185m	5	0		
Molybdenum	ppm	ASTM D5185m	5	<1		
Manganese	ppm	ASTM D5185m		0		
Magnesium	ppm	ASTM D5185m	25	2		
Calcium	ppm	ASTM D5185m	200	52		
Phosphorus	ppm	ASTM D5185m	300	250		
Zinc	ppm	ASTM D5185m	370	299		
Sulfur	ppm	ASTM D5185m	2500	771		
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>20	<1		
Sodium	ppm	ASTM D5185m		2		
Potassium	ppm		>20	0		
FLUID CLEANLIN	ESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647		8352		
Particles >6µm		ASTM D7647	>2500	1289		
Particles >14µm		ASTM D7647	>320	76		
Particles >21µm		ASTM D7647	>80	16		
Particles >38µm		ASTM D7647	>20	1		
Particles >71µm		ASTM D7647	>4	0		
Oil Cleanliness		ISO 4406 (c)	>18/15	17/13		
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045	0.57	0.30		
9:55:07) Rev: 1					act/Location: 2 (	- WESCHEMO

Report Id: WESCHEMO [WUSCAR] 06234847 (Generated: 07/15/2024 09:55:07) Rev: 1


Contact/Location: ? ? - WESCHEMO Page 1 of 2





## **OIL ANALYSIS REPORT**











Test Package : MOB 2

Laboratory

Sample No.

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Report Id: WESCHEMO [WUSCAR] 06234847 (Generated: 07/15/2024 09:55:07) Rev: 1

Certificate 12367

Contact/Location: ? ? - WESCHEMO

kohmes@rocktenn.com

Page 2 of 2

T:

F: