

OIL ANALYSIS REPORT



Machine Id

5918851 (S/N 1536)

Compressor Fluid KAESER SIGMA (OEM) M-460 (--- GAL)

DIAGNOSIS

Recommendation

Oil and filter change at the time of sampling has been noted. No corrective action is recommended at this time. Resample at the next service interval to monitor. We were unable to perform a particle count due to a high concentration of particles present in this sample.

Wear

All component wear rates are normal.

Contamination

Moderate concentration of visible dirt/debris present in the oil.


Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.


SAMPLE INFORM	IATION	method	limit/base	current	history1	history2
Sample Number		Client Info		KCPA017456		
Sample Date		Client Info		08 Jul 2024		
Machine Age	hrs	Client Info		34527		
Oil Age	hrs	Client Info		0		
Oil Changed		Client Info		Changed		
Sample Status				ABNORMAL		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	<1		
Chromium	ppm	ASTM D5185m	>10	0		
Nickel	ppm	ASTM D5185m	>3	<1		
Titanium	ppm	ASTM D5185m	>3	0		
Silver	ppm	ASTM D5185m	>2	0		
Aluminum	ppm	ASTM D5185m	>10	<1		
Lead	ppm	ASTM D5185m	>10	0		
Copper	ppm	ASTM D5185m	>50	12		
Tin	ppm	ASTM D5185m	>10	<1		
Vanadium	ppm	ASTM D5185m		0		
Cadmium	ppm	ASTM D5185m		0		
ADDITIVES		method	limit/base	current	history1	history2
ADDITIVES Boron	ppm	method ASTM D5185m	limit/base	current 0	history1	history2
	ppm ppm					
Boron		ASTM D5185m	0	0		
Boron Barium	ppm	ASTM D5185m ASTM D5185m	0 90	0 0		
Boron Barium Molybdenum	ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m	0 90	0 0 0		
Boron Barium Molybdenum Manganese	ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	0 90 0	0 0 0 0		
Boron Barium Molybdenum Manganese Magnesium	ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	0 90 0 100	0 0 0 0 0		
Boron Barium Molybdenum Manganese Magnesium Calcium	ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	0 90 0 100 0	0 0 0 0 0 0	 	
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus	ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	0 90 0 100 0 0	0 0 0 0 0 0 0 0	 	
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc	ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	0 90 0 100 0 0 0	0 0 0 0 0 0 0 <1	 	
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur	ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	0 90 0 100 0 0 23500	0 0 0 0 0 0 0 0 <1 21407		
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINANTS	ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	0 90 0 100 0 0 23500 limit/base	0 0 0 0 0 0 0 0 21407 current	 history1	 history2
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINANTS Silicon	ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m method ASTM D5185m	0 90 0 100 0 0 23500 limit/base	0 0 0 0 0 0 0 0 0 21407 21407 current	 history1	 history2
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINANTS Silicon Sodium	ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m method ASTM D5185m	0 90 0 100 0 0 23500 limit/base >25	0 0 0 0 0 0 0 0 0 2 1407 21407 21407 21407	 history1	 history2
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINANTS Silicon Sodium Potassium	ppm ppm ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m	0 90 0 100 0 0 23500 limit/base >25	0 0 0 0 0 0 <1 21407 current <1 1 1	 history1	 history2
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINANTS Silicon Sodium Potassium Water	ppm ppm ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m	0 90 0 100 0 0 23500 limit/base >25 >20 >20	0 0 0 0 0 0 <1 21407 current <1 1 1 <1 0.038		 history2



OIL ANALYSIS REPORT







	VISUAL		method	limit/base	current	history1	history2
	White Metal	scalar	*Visual	NONE	NONE		
	Yellow Metal	scalar	*Visual	NONE	NONE		
	Precipitate	scalar	*Visual	NONE	NONE		
	Silt	scalar	*Visual	NONE	NONE		
	Debris	scalar	*Visual	NONE			
4	Sand/Dirt	scalar	*Visual	NONE	NONE		
Jul8/24	Appearance	scalar	*Visual	NORML	NORML		
	Odor Emulsified Water	scalar scalar	*Visual *Visual	NORML >0.05	NORML NEG		
	Free Water	scalar	*Visual	>0.05	NEG		
	FLUID PROPERT		method	limit/base			
					current	history1	history2
	Visc @ 40°C	cSt	ASTM D445		49.0		
	SAMPLE IMAGES	S	method	limit/base	current	history1	history2
Jul8/24	Color					no image	no image
	Bottom					no image	no image
1.181-11	Ed 4			Jul8/24			
	Non-ferrous Metal	5		Jul8/24			
	Viscosity @ 40°C			Jul8/24 Acid Number 1.0 Acid Number 0.0 1.1 1.1 1.1 1.1 1.1 1.1 1.1	Acid Number		
ique Number st Package	: WearCheck USA - 50 : KCPA017456 : 06234962 : 11123796 : IND 2 (Additional Test contact Customer Serv	Recei Teste Diagr tts: KF, P ice at 1-8	ived : 12 id : 15 inosed : 15 intCount) 800-237-1369	2 Jul 2024 5 Jul 2024 Jul 2024 - Dor	n Baldridge	Cc	UPS S HARLAN RE LATHROP, CA US 9533(ontact: J. BILAL jbilal@ups.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Report Id: UPSLAT [WUSCAR] 06234962 (Generated: 07/15/2024 21:39:50) Rev: 1

Certificate L2367

Contact/Location: J. BILAL - UPSLAT Page 2 of 2

T:

F: