

### **OIL ANALYSIS REPORT**

#### \_\_

### NORMAL



# STL64.1

## **STL 64-1 RECOILER REDUCER (S/N 16-5130-0305)**

Gearbox

NOT GIVEN (--- QTS)

### DIAGNOSIS

Recommendation

Little or no information is provided as to the component and lubricant being tested. Recommendations are therefore generic in nature and may not apply to the current application. Please forward information as to equipment type, reservoir capacity, lubricant type and any pertinent information to allow for a more accurate assessment. Resample at the next service interval to monitor. NOTE: Please provide information regarding reservoir capacity, filter type and micron rating with next sample. Please specify the brand, type, and viscosity of the oil on your next sample.

#### Wear

All component wear rates are normal.

#### Contamination

The water content is negligible. There is no indication of any contamination in the oil.

#### **Fluid Condition**

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

-				

Sample Rating Trend

SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		RP0044000	RP0038585	RP0034544
Sample Date		Client Info		11 Jul 2024	03 Oct 2023	25 Apr 2023
Machine Age	hrs	Client Info		0	0	0
Oil Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		N/A	N/A	N/A
Sample Status				NORMAL	NORMAL	NORMAL
WEAR METALS		method	limit/base	current	history1	history2
PQ		ASTM D8184		69	79	60
Iron	ppm	ASTM D5185m	>200	91	93	85
Chromium	ppm	ASTM D5185m	>15	<1	<1	<1
Nickel	ppm	ASTM D5185m	>15	0	0	0
Titanium	ppm	ASTM D5185m		<1	<1	<1
Silver	ppm	ASTM D5185m		0	0	0
Aluminum	ppm	ASTM D5185m	>25	2	<1	0
Lead	ppm	ASTM D5185m	>100	0	0	0
Copper	ppm	ASTM D5185m	>200	3	3	2
Tin	ppm	ASTM D5185m	>25	<1	<1	0
Vanadium	ppm	ASTM D5185m		0	<1	0
Cadmium	ppm	ASTM D5185m		0	<1	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		3	<1	1
Barium	ppm	ASTM D5185m		0	0	0
Molybdenum	ppm	ASTM D5185m		0	1	0
Manganese	ppm	ASTM D5185m		<1	1	<1
Magnesium	ppm	ASTM D5185m		0	1	<1
Calcium	ppm	ASTM D5185m		27	57	33
Phosphorus	ppm	ASTM D5185m		112	127	109
Zinc	ppm	ASTM D5185m		0	8	8
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>50	5	4	5
Sodium	ppm	ASTM D5185m		<1	<1	0
Potassium	ppm	ASTM D5185m	>20	1	1	1
Water	%	ASTM D6304	>0.2	0.005	0.006	0.012
ppm Water	ppm	ASTM D6304	>2000	52	65.3	127.9
FLUID DEGRADA	TION	method	limit/base	current	history1	history2

Acid Number (AN)

mg KOH/g ASTM D8045


0.29


0.32


0.29



### **OIL ANALYSIS REPORT**







VISUAL		method				history2
White Metal	scalar	*Visual	NONE	NONE	NONE	MODER
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
<b>Emulsified Water</b>	scalar	*Visual	>0.2	NEG	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG	NEG
FLUID DDODEDT	TEO.		12 21 //		111	1:
FLUID PROPERT	IES.	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445		215	218	218

Color **Bottom** 

SAMPLE IMAGES



**GRAPHS** Ferrous Alloys PQ 150 220 100 160 140 2<sup>120</sup> 100 Non-ferrous Metals Viscosity @ 40°C Acid Number 260 (B/HO.50 NO.40 240 Ē 0.30 흩 0.20 ₹ 0.10 200 0.00 PG 180



PO

100



Certificate 12367

Laboratory Sample No.

: RP0044000 Lab Number : 06235049

Unique Number : 11123883

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Received : 12 Jul 2024 **Tested** : 15 Jul 2024

Diagnosed : 15 Jul 2024 - Wes Davis Test Package : IND 2 ( Additional Tests: PQ )

To discuss this sample report, contact Customer Service at 1-800-237-1369. \* - Denotes test methods that are outside of the ISO 17025 scope of accreditation. **OUTOKUMPU STAINLESS USA** 

HWY 43 N CALVERT, AL US 36513

Contact: MARIO JOHNSON Mario.johnson@outokumpu.com T: (251)321-4105

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

F: x: