


OIL ANALYSIS REPORT



OKLAHOMA/102/DE - OTHER SERVICE 38.85 [OKLAHOMA^102^DE - OTHER SERVICE]

Diesel Engine

MOBIL DELVAC 1300 SUPER15W40 (--- GAL)





DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

All component wear rates are normal.

Contamination

There is no indication of any contamination in the


Fluid Condition


The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.


SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0945525	WC0935213	WC0862629
Sample Date		Client Info		03 Jul 2024	26 Apr 2024	23 Oct 2023
Machine Age	hrs	Client Info		4630	4305	3661
Oil Age	hrs	Client Info		325	644	121
Oil Changed		Client Info		Changed	Changed	Changed
Sample Status				NORMAL	NORMAL	NORMAL
CONTAMINATIO	N	method	limit/base	current	history1	history2
Fuel		WC Method	>5	<1.0	<1.0	<1.0
Water		WC Method	>0.2	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>100	23	50	69
Chromium	ppm	ASTM D5185m	>20	<1	1	2
Nickel	ppm	ASTM D5185m	>2	0	<1	0
Titanium	ppm	ASTM D5185m	>2	0	<1	0
Silver	ppm	ASTM D5185m	>2	0	0	0
Aluminum	ppm	ASTM D5185m	>25	1	2	3
Lead	ppm	ASTM D5185m	>40	0	2	3
Copper	ppm		>330	3	8	10
Tin	ppm	ASTM D5185m	>15	0	1	1
Vanadium	ppm	ASTM D5185m	710	0	<1	0
Cadmium	ppm	ASTM D5185m		0	<1	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	0	28	29	18
Barium	ppm	ASTM D5185m		0	2	0
Molybdenum	ppm	ASTM D5185m	0	39	42	40
Manganese	ppm	ASTM D5185m		<1	<1	<1
Magnesium	ppm	ASTM D5185m	0	491	470	484
Calcium	ppm	ASTM D5185m		1801	1651	1717
Phosphorus	ppm	ASTM D5185m		783	789	970
Zinc	ppm	ASTM D5185m		894	910	1062
Sulfur	ppm	ASTM D5185m		2835	2547	2539
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m		5	7	8
Sodium	ppm	ASTM D5185m		3	0	6
Potassium	ppm	ASTM D5185m	>20	0	2	<1
INFRA-RED		method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844	>3	0.5	0.8	1
Nitration	Abs/cm	*ASTM D7624	>20	8.5	11.0	12.6
Sulfation	Abs/.1mm	*ASTM D7624	>30	8.5 22.5	23.2	24.2
				,		
FLUID DEGRADA	ATION _	method	limit/base	current	history1	history2
FLUID DEGRADA		method	limit/base	current	history1	history2
FLUID DEGRADA Oxidation Base Number (BN)	ATION Abs/.1mm mg KOH/g	method *ASTM D7414 ASTM D2896	>25	20.8 9.7	history1 23.2 8.3	history2 24.3 8.3



OIL ANALYSIS REPORT











VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG	NEG

FLUID PROPER	TIES	method				history2
Visc @ 100°C	cSt	ASTM D445	14	12.9	13.1	12.9













Certificate 12367

Laboratory Sample No.

: WC0945525 Lab Number : 06235717 Unique Number : 11124551

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Received **Tested**

: 15 Jul 2024 : 16 Jul 2024 Diagnosed

SHERWOOD CONSTRUCTION CO INC 3219 WEST MAY ST WICHITA, KS US 67213

: 16 Jul 2024 - Wes Davis Test Package : CONST (Additional Tests: TBN)

Contact: DOUG KING doug.king@sherwood.net T: (316)617-3161

To discuss this sample report, contact Customer Service at 1-800-237-1369. * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

F: x: