

OIL ANALYSIS REPORT

NORMAL

Machine Id **155XX067** Component **Hydraulic System** Fluid **ROYAL PURPLE SYNFILM GT 46 (--- GAL)**

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor. NOTE: Please provide information regarding reservoir capacity, filter type and micron rating with next sample.

Wear


All component wear rates are normal.

Contamination

The system cleanliness is acceptable for your target ISO 4406 cleanliness code. The water content is negligible. The system and fluid cleanliness is acceptable.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.








SAMPLE INFORM	IATION	method	limit/base	current	history1	history2
Sample Number		Client Info		RP0042946	RP0008462	RP0000822
Sample Date		Client Info		02 Jul 2024	20 Mar 2024	25 Jan 2023
Machine Age	hrs	Client Info		0	0	0
Oil Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		N/A	N/A	N/A
Sample Status				NORMAL	NORMAL	ABNORMAL
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>20	<1	<1	<1
Chromium	ppm	ASTM D5185m	>20	<1	0	0
Nickel	ppm	ASTM D5185m	>20	<1	0	0
Titanium	ppm	ASTM D5185m		<1	0	0
Silver	ppm	ASTM D5185m		0	0	0
Aluminum	ppm	ASTM D5185m	>20	2	1	0
Lead	ppm	ASTM D5185m	>20	<1	0	0
Copper	ppm	ASTM D5185m	>20	3	1	<1
Tin	ppm	ASTM D5185m	>20	<1	0	0
Vanadium	ppm	ASTM D5185m		0	0	0
Cadmium	ppm	ASTM D5185m		<1	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	0	0	0	0
Barium	ppm	ASTM D5185m		0	<1	0
Molybdenum	ppm	ASTM D5185m	0	<1	0	0
Manganese	ppm	ASTM D5185m	U	0	0	0
Magnesium	ppm	ASTM D5185m	95	3	3	2
Calcium	ppm	ASTM D5185m	0	0	4	0
Phosphorus	ppm	ASTM D5185m	0	0	0	6
Zinc	ppm		0	6	3	6
-				-		
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>15	2	<1	<1
Sodium	ppm	ASTM D5185m		0	0	0
Potassium	ppm	ASTM D5185m	>20	1	1	<1
Water	%	ASTM D6304	>0.05	0.007	0.003	▲ 0.291
ppm Water	ppm	ASTM D6304		73	35	A 2910
FLUID CLEANLIN	IESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647		265	2182	1479
Particles >6µm		ASTM D7647	>1300	84	700	806
Particles >14µm		ASTM D7647	>160	17	63	137
Particles >21µm		ASTM D7647		4	20	46
Particles >38µm		ASTM D7647	>10	1	0	7
Particles >71µm		ASTM D7647	>3	0	0	1
Oil Cleanliness		ISO 4406 (c)	>/17/14	15/14/11	18/17/13	18/17/14
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045		0.18	0.17	0.16





OIL ANALYSIS REPORT












VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	LIGHT	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.05	NEG	NEG	0.2%
Free Water	scalar	*Visual		NEG	NEG	NEG
FLUID PROPERT	IES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445	46.0	42.0	42.5	33.0
SAMPLE IMAGES	S	method	limit/base	current	history1	history2
Color						

Bottom



: 16 Jul 2024 : 16 Jul 2024 - Wes Davis

VANCEBORO, NC S US 28586 Contact: DOUG WEIR Doug.Weir@ipaper.com;jon.fazenbaker@wearcheck.com T: (252)633-7350 CGM 106:2012) F: (252)633-7761

To discuss this sample report, contact Customer Service at 1-800-237-1369. * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Unique Number : 11124767

Test Package : IND 2

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Diagnosed

Report Id: WEYNEW [WUSCAR] 06235933 (Generated: 07/16/2024 09:43:31) Rev: 1

Certificate 12367

Contact/Location: DOUG WEIR - WEYNEW