


OIL ANALYSIS REPORT

Sample Rating Trend



Machine Id
C-38
Component
Screw Compressor

INGERSOLL-RAND SSR ULTRA COOLANT (--- GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is a trace of moisture present in the oil. The amount and size of particulates present in the system are acceptable.


Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.


militizz Aprilitizz Auglitizz Diechitzz Miniferza Minife						
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0711810	WC0711816	WC0820307
Sample Date		Client Info		09 Jul 2024	04 Jun 2024	01 May 2024
Machine Age	days	Client Info		0	0	0
Oil Age	days	Client Info		0	0	0
Oil Changed		Client Info		N/A	N/A	N/A
Sample Status				MARGINAL	NORMAL	NORMAL
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>60	2	1	<1
Chromium	ppm	ASTM D5185m	>4	<1	0	0
Nickel	ppm	ASTM D5185m		2	1	2
Titanium	ppm	ASTM D5185m		<1	0	0
Silver	ppm	ASTM D5185m		0	0	0
Aluminum	ppm	ASTM D5185m	>5	2	0	0
Lead	ppm	ASTM D5185m	>10	<1	0	<1
Copper	ppm	ASTM D5185m	>30	<1	<1	0
Tin	ppm	ASTM D5185m	>15	<1	<1	<1
Vanadium	ppm	ASTM D5185m		0	<1	0
Cadmium	ppm	ASTM D5185m		<1	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	0	0	0	0
Barium	ppm	ASTM D5185m	500	757	791	776
Molybdenum	ppm	ASTM D5185m	0	<1	0	0
Manganese	ppm	ASTM D5185m		0	0	<1
Magnesium	ppm	ASTM D5185m	0	<1	0	1
Calcium	ppm	ASTM D5185m	0	0	2	6
Phosphorus	ppm	ASTM D5185m	20	39	63	66
Zinc	ppm	ASTM D5185m	0	0	0	0
Sulfur	ppm	ASTM D5185m	200	257	384	377
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>50	3	3	3
Sodium	ppm	ASTM D5185m		1	2	1
Potassium	ppm	ASTM D5185m		1	<1	2
Water	%	ASTM D6304	>0.1	<u> </u>	0.065	0.071
ppm Water	ppm	ASTM D6304	>1000	<u> </u>	653	712
FLUID CLEANLIN	IESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>10000	275	154	7266
Particles >6µm		ASTM D7647	>2500	60	44	1270
Particles >14μm		ASTM D7647	>320	8	3	16
Particles >21µm		ASTM D7647	>80	3	1	5
Particles >38µm		ASTM D7647	>20	0	0	0
Particles >71μm		ASTM D7647	>4	0	0	0
Oil Cleanliness		ISO 4406 (c)	>20/18/15	15/13/10	14/13/9	20/17/11
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045		0.057	0.067	0.055





OIL ANALYSIS REPORT



Ok - Aunt	- 4μm 6μm		 		
8k +	14µ1	n			
6k -					٨
4k -					1
2k -		1			11
_	-	N		Thursday.	N
Ok Lanna					







VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.1	NEG	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG	NEG
FLUID PROPERT	TEQ	method	limit/base	current	history1	history2
FLUID FNOFEN I	IES	method	IIIIII/Dase	Current	HISTOLAL	HISTORYZ
Visc @ 40°C	cSt	ASTM D445	49.4	48.5	48.8	49.3

SAMPLE IMAGES

method

limit/base

current

history1

history2

Bottom

Color





GRAPHS Particle Count Ferrous Alloys 491 520 122,88 30.72 1,920 Non-ferrous Metals 480 120 Viscosity @ 40°C Acid Number 2.50 2.00 (mg KOH/g) 1.50 1.00 0.50 ₹ 50 0.00 Acid 1





Laboratory Sample No.

: WC0711810

Lab Number : 06235941 Unique Number : 11124775

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Received : 15 Jul 2024 **Tested**

: 16 Jul 2024 Diagnosed : 16 Jul 2024 - Don Baldridge

UGI ENERGY SERVICES - LNG FACILITY 80 ENERGY LN MESHOPPEN, PA US 18630 Contact: JOE BARRETT

jbarrett@ugies.com

Test Package : IND 2 (Additional Tests: KF, PrtCount) Certificate 12367 To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:

F: