


# **OIL ANALYSIS REPORT**

Sample Rating Trend



Machine Id

# KAESER DSD 175 4434887 (S/N 1032)

Compressor

KAESER SIGMA (OEM) S-460 (--- GAL)

#### Recommendation

No corrective action is recommended at this time. The filter change at the time of sampling has been noted. Resample at the next service interval to monitor.

#### Wear

All component wear rates are normal.

### Contamination

There is a moderate amount of silt (particulates < 14 microns in size) present in the oil.

#### Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

		Oct2018	Feb2019 Oct2019	Mar2021 Sep2022 Jul2023	Jun2024	
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		KCPA017922	KCPA004587	KCP48368
Sample Date		Client Info		19 Jun 2024	20 Jul 2023	05 Sep 2022
Machine Age	hrs	Client Info		82762	75402	0
Oil Age	hrs	Client Info		600	0	0
Oil Changed		Client Info		Not Changd	N/A	N/A
Sample Status				ATTENTION	NORMAL	ABNORMAL
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	<1	0	1
Chromium	ppm	ASTM D5185m	>10	0	0	0
Nickel	ppm	ASTM D5185m	>3	0	0	0
Titanium	ppm	ASTM D5185m	>3	0	0	0
Silver	ppm	ASTM D5185m	>2	0	0	0
Aluminum	ppm	ASTM D5185m	>10	1	0	<1
Lead	ppm	ASTM D5185m	>10	0	0	0
Copper	ppm	ASTM D5185m	>50	2	13	5
Tin	ppm	ASTM D5185m	>10	0	0	<1
Antimony	ppm	ASTM D5185m				
Vanadium	ppm	ASTM D5185m		0	0	0
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0	0	0
Barium	ppm	ASTM D5185m	90	0	2	2
Molybdenum	ppm	ASTM D5185m		0	0	0
Manganese	ppm	ASTM D5185m		0	0	0
Magnesium	ppm	ASTM D5185m	90	0	0	1
Calcium	ppm	ASTM D5185m	2	0	0	0
Phosphorus	ppm	ASTM D5185m		0	0	4
Zinc	ppm	ASTM D5185m		0	0	0
Sulfur	ppm	ASTM D5185m		19255	17195	10339
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	0	0	0
Sodium	ppm	ASTM D5185m		3	0	0
Potassium	ppm	ASTM D5185m	>20	1	<1	1
Water	%	ASTM D6304		0.007	0.005	0.010
ppm Water	ppm	ASTM D6304	>500	76	50.1	101.2
FLUID CLEANLIN	ESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647		9289	285	14534
Particles >6µm		ASTM D7647	>1300	<u> </u>	86	<u></u> 3570
Particles >14μm		ASTM D7647	>80	26	8	<u>408</u>
Particles >21µm		ASTM D7647	>20	6	3	<u>113</u>
Particles >38µm		ASTM D7647	>4	0	0	<u> </u>
Particles >71µm		ASTM D7647	>3	0	0	0
Oil Cleanliness		ISO 4406 (c)	>/17/13	<b>20/18/12</b>	15/14/10	<u>21/19/16</u>
FLUID DEGRADA	TION	method	limit/base	current	history1	history2



## **OIL ANALYSIS REPORT**







Laboratory

Sample No. Lab Number

: KCPA017922 : 06235988 Unique Number : 11124822

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Received : 15 Jul 2024

**Tested** : 16 Jul 2024 Diagnosed

: 17 Jul 2024 - Don Baldridge

US 75203 Contact: SERVICE MANAGER

1120 E CLARENDON DR

WEST ROCK CONVERTING COMPANY

Test Package : IND 2 ( Additional Tests: KF, PrtCount ) Certificate 12367 To discuss this sample report, contact Customer Service at 1-800-237-1369.

 $^st$  - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:

F:

DALLAS, TX