

# **OIL ANALYSIS REPORT**

Sample Rating Trend



# Area **WEARGUARD ISO 32 [1499]** ITJ130123 - BLACK HAWK Component Compressor

## Recommendation

Oil and filter change at the time of sampling has been noted. Resample at the next service interval to monitor.

## Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the oil.


## Fluid Condition


The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

SAMPLE INFORM	<b>IATION</b>	method	limit/base	current	history1	history2
Sample Number		Client Info		UCH06236148		
Sample Date		Client Info		01 Jul 2024		
Machine Age	hrs	Client Info		3550		
Oil Age	hrs	Client Info		0		
Oil Changed		Client Info		Changed		
Sample Status				NORMAL		
CONTAMINATIO	N	method	limit/base	current	history1	history2
Water		WC Method	>0.1	NEG		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	2		
Chromium	ppm	ASTM D5185m	>10	0		
Nickel	ppm	ASTM D5185m		0		
Titanium	ppm	ASTM D5185m		0		
Silver	ppm	ASTM D5185m		0		
Aluminum	ppm	ASTM D5185m	>25	<1		
Lead	ppm	ASTM D5185m	>25	0		
Copper	ppm	ASTM D5185m	>50	0		
Tin	ppm	ASTM D5185m	>15	0		
Vanadium	ppm	ASTM D5185m		0		
Cadmium	ppm	ASTM D5185m		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0		
Barium	ppm	ASTM D5185m		2		
Molybdenum	ppm	ASTM D5185m		<1		
Manganese	ppm	ASTM D5185m		0		
Magnesium	ppm	ASTM D5185m		2		
Calcium	ppm	ASTM D5185m		0		
Phosphorus	ppm	ASTM D5185m		108		
Zinc	ppm	ASTM D5185m		91		
Sulfur	ppm	ASTM D5185m		3654		
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	1		
Sodium	ppm	ASTM D5185m		3		
Potassium	ppm	ASTM D5185m	>20	<1		
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045		0.27		



# **OIL ANALYSIS REPORT**





	VISUAL		method	limit/base	current	nistory i	nistory2
	White Metal	scalar	*Visual	NONE	NONE		
	Yellow Metal	scalar	*Visual	NONE	NONE		
	Precipitate	scalar	*Visual	NONE	NONE		
	Silt	scalar	*Visual	NONE	LIGHT		
	Debris	scalar	*Visual	NONE	LIGHT		
	Sand/Dirt	scalar	*Visual	NONE	NONE		
Jul1/24	Appearance	scalar	*Visual	NORML	NORML		
J.	Odor	scalar	*Visual	NORML	NORML		
	Emulsified Water	scalar	*Visual	>0.1	NEG		
1	Free Water	scalar	*Visual		NEG		
	FLUID PROPERT	IES	method	limit/base	current	history1	history2
	Visc @ 40°C	cSt	ASTM D445		37.1		
	SAMPLE IMAGES		method	limit/base	current	history1	history2
		<i>.</i>	mothod	intersection			
Jult,24 +	Color					no image	no image
	Bottom					no image	no image
	Non-ferrous Metal	s		Jul1/24 8			
	udd 6 4			Jult/24			
	Viscosity @ 40°C			7	Acid Number		
	55 50 2			() () () () () () () () () () () () () (	1		
	다. 9 45 - 정 40 - <mark>Abnormal</mark>			4 0.13 N p 0.00	5		
				Jul1/24	4		



Report Id: UCTOTSAI [WUSCAR] 06236148 (Generated: 07/17/2024 12:12:07) Rev: 1

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Contact/Location: Jeremy Weimer - UCTOTSAI

F: