

OIL ANALYSIS REPORT

Sample Rating Trend

WEAR

Machine Id HIPERBARIC NOT GIVEN WC0820219

Component Hydraulic System

Fluid {not provided} (114 GAL)

DIAGNOSIS

Recommendation

No corrective action is recommended at this time. Resample at the next service interval to monitor. Please specify the brand, type, and viscosity of the oil on your next sample.

📥 Wear

The iron level is abnormal. All other component wear rates are normal.

Contamination

There is a moderate amount of silt (particulates < 14 microns in size) present in the oil.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is acceptable for the time in service.


				Jul2024		
SAMPLE INFORM	ATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0820219		
Sample Date		Client Info		09 Jul 2024		
Machine Age	hrs	Client Info		115942		
Oil Age	hrs	Client Info		0		
Oil Changed		Client Info		N/A		
Sample Status				ABNORMAL		
CONTAMINATION	N	method	limit/base	current	history1	history2
Water		WC Method	>0.05	NEG		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>20	4 3		
Chromium	ppm	ASTM D5185m	>20	0		
Nickel	ppm	ASTM D5185m	>20	0		
Titanium	ppm	ASTM D5185m		0		
Silver	ppm	ASTM D5185m		0		
Aluminum	ppm	ASTM D5185m	>20	0		
Lead	ppm	ASTM D5185m	>20	0		
Copper	ppm	ASTM D5185m	>20	6		
Tin	ppm	ASTM D5185m	>20	0		
Vanadium	ppm	ASTM D5185m	200	0		
Cadmium	ppm	ASTM D5185m		0		
	ppm		Page 10 /00 - 10 - 10	-		
ADDITIVES		method	limit/base		history1	history2
Boron	ppm	ASTM D5185m		0		
Barium	ppm	ASTM D5185m		0		
Molybdenum	ppm	ASTM D5185m		0		
Vanganese	ppm	ASTM D5185m		<1		
Magnesium	ppm	ASTM D5185m		2		
Calcium	ppm	ASTM D5185m		<1		
Phosphorus	ppm	ASTM D5185m		630		
Zinc	ppm	ASTM D5185m		20		
Sulfur	ppm	ASTM D5185m		584		
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>15	1		
Sodium	ppm	ASTM D5185m		2		
Potassium	ppm	ASTM D5185m	>20	0		
FLUID CLEANLIN	IESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>5000	6574		
Particles >6µm		ASTM D7647	>1300	1274		
Particles >14µm		ASTM D7647	>160	87		
		ASTM D7647	>40	22		
				2		
Particles >21µm		ASTM D7647	>10	2		
Particles >21µm Particles >38µm		ASTM D7647 ASTM D7647		0		
Particles >21μm Particles >38μm Particles >71μm Oil Cleanliness						
Particles >21µm Particles >38µm Particles >71µm Oil Cleanliness		ASTM D7647	>3	0 ● 20/17/14		
Particles >21μm Particles >38μm Particles >71μm	<mark>∖TION</mark> mg KOH/g	ASTM D7647 ISO 4406 (c)	>3 >19/17/14	0 ● 20/17/14		


Report Id: UNIMIRCA [WUSCAR] 06236795 (Generated: 07/17/2024 14:49:41) Rev: 1


Contact/Location: Service Manager - UNIMIRCA Page 1 of 2



OIL ANALYSIS REPORT









	VISUAL		method	limit/base	current	history1	history
	White Metal	scalar	*Visual	NONE	NONE		
	Yellow Metal	scalar	*Visual	NONE	NONE		
	Precipitate	scalar	*Visual	NONE	NONE		
	Silt	scalar	*Visual	NONE	NONE		
	Debris	scalar	*Visual	NONE	NONE		
	Sand/Dirt	scalar	*Visual	NONE	NONE		
	Appearance	scalar	*Visual	NORML	NORML		
	Odor	scalar	*Visual	NORML	NORML		
	Emulsified Water	scalar	*Visual	>0.05	NEG		
	Free Water	scalar	*Visual		NEG		
	FLUID PROPER	RTIES	method	limit/base	current	history1	histor
	Visc @ 40°C	cSt	ASTM D445		46.7		
	SAMPLE IMAG	ES	method	limit/base	current	history1	history
	Color					no image	no imag
					A BA		
	Bottom					no image	no imag
	GRAPHS						
	Ferrous Alloys 50 T			491,520	Particle Coun	ıt	
	40 iron						
	seeses chromium			122,880			
100	30 - nickel			30,720	pevere		
	10-						
	0				Abnormal		
	Jul9/24			Jul9/24. 056'1 ml)		N	
		alc		42/6lin 480 120		Ţ.	
	Non-ferrous Met	a15		of part			
	8 - copper			ja 120	-	1	
	E 6			30			
	1					/	
	2						\ · · · · · · · · · · · · · · · · · · ·
	19/24			19/24			1
	Jul9/24	_		Jul9/24		14µ 21µ	38µ
		2		04	Acid Number		38µ
	Viscosity @ 40°(2		04	Acid Number		38µ
	Viscosity @ 40°(C		04	Acid Number		38µ
	Viscosity @ 40°(2		04	Acid Number		38µ
	Viscosity @ 40°(2		04	Acid Number		38µ
	Viscosity @ 40°(42(GInr (0)400.48 (0)400,48 (0)400,48 (0)400,48 (0)40,48)(0)40,48)	Acid Number		звµ



To discuss this sample report, contact Customer Service at 1-800-237-1369. * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Test Package : IND 2

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Certificate 12367

Contact/Location: Service Manager - UNIMIRCA

T:

F:

Contact: Service Manager