

OIL ANALYSIS REPORT

Machine Id KAESER SK-19 2168804 (S/N 1681)

Component Compressor Fluid KAESER SIGMA (OEM) S-460 (--- GAL)

Recommendation

No corrective action is recommended at this time. The filter change at the time of sampling has been noted. Resample at the next service interval to monitor.

Wear


All component wear rates are normal.

Contamination

There is a moderate amount of particulates present in the oil.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.




SAMPLE INFORM	IATION	method	limit/base	current	history1	history2
Sample Number		Client Info		KCPA011853	KCPA002184	KC104272
Sample Date		Client Info		28 Jun 2024	16 Jun 2023	23 May 2022
Machine Age	hrs	Client Info		77857	75508	72943
Oil Age	hrs	Client Info		0	0	1677
Oil Changed		Client Info		N/A	N/A	Not Changd
Sample Status				ATTENTION	NORMAL	ATTENTION
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	0	<1	<1
Chromium	ppm	ASTM D5185m	>10	0	0	0
Nickel	ppm	ASTM D5185m	>3	0	0	0
Titanium	ppm	ASTM D5185m	>3	0	0	0
Silver	ppm	ASTM D5185m	>2	0	0	0
Aluminum	ppm	ASTM D5185m	>10	0	0	<1
Lead	ppm	ASTM D5185m	>10	0	0	<1
Copper	ppm		>50	9	8	6
Tin	ppm	ASTM D5185m	>10	0	<1	0
Antimony	ppm	ASTM D5185m				
Vanadium	ppm	ASTM D5185m		0	0	0
Cadmium	ppm	ASTM D5185m		0	0	0
	ppill		1	-	-	-
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0	0	0
Barium	ppm	ASTM D5185m	90	0	<1	13
Molybdenum	ppm	ASTM D5185m		0	0	0
Manganese	ppm	ASTM D5185m		0	<1	<1
Magnesium	ppm	ASTM D5185m	90	18	24	50
Calcium	ppm	ASTM D5185m	2	0	0	2
Phosphorus	ppm	ASTM D5185m		3	2	2
Zinc	ppm	ASTM D5185m		65	55	35
Sulfur	ppm	ASTM D5185m		18393	18361	19156
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	2	3	2
Sodium	ppm	ASTM D5185m		14	11	22
Potassium	ppm	ASTM D5185m	>20	1	2	4
Water	%	ASTM D6304	>0.05	0.015	0.014	0.034
ppm Water	ppm	ASTM D6304	>500	156	146.1	343.8
FLUID CLEANLIN	ESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647		4856	2071	22550
Particles >6µm		ASTM D7647	>1300	<mark> </mark> 1380	357	1428
Particles >14µm		ASTM D7647	>80	<mark> </mark> 113	13	64
Particles >21µm		ASTM D7647	>20	<mark> </mark> 27	3	16
Particles >38µm		ASTM D7647	>4	1	0	1
Particles >71µm		ASTM D7647	>3	0	0	0
Oil Cleanliness		ISO 4406 (c)	>/17/13	e 19/18/14	18/16/11	22/18/13
FLUID DEGRADA		method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g		0.4	0.32	0.328 ct/Location: BBI	0.35


Report Id: CABWIL [WUSCAR] 06236829 (Generated: 07/17/2024 15:02:40) Rev: 1


Contact/Location: BRIAN ? - CABWIL




OIL ANALYSIS REPORT










VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.05	NEG	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG	NEG
FLUID PROPER	TIES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445	46	42.7	44.3	44.0
SAMPLE IMAGE	S	method	limit/base	current	history1	history2
Color						
Bottom						

Bottom





To discuss this sample report, contact Customer Service at 1-800-237-1369. * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Report Id: CABWIL [WUSCAR] 06236829 (Generated: 07/17/2024 15:02:40) Rev: 1

Contact/Location: BRIAN ? - CABWIL

BRIAN@CABLETECHNOLOGYINC.COM

Page 2 of 2

Т:

F: