




OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL



Machine Id
03-0358 2020 INTERNATIONAL
 Component
Diesel Engine
 Fluid
PETRO CANADA 10W30 (--- GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor. Please specify the component make and model with your next sample.

Wear

All component wear rates are normal.

Contamination

Elevated aluminum (Al) and/or lead (Pb) and potassium (K) levels in your metals analysis are likely a result of solder flux release into the lubricant and is common on new equipment/components. There is no indication of any contamination in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION		method	limit/base	current	history1	history2
Sample Number	Client Info			SBP0007099	SBP0004886	SBP0003728
Sample Date	Client Info			11 Jul 2024	26 Oct 2023	21 Apr 2023
Machine Age	hrs	Client Info		1640	1043	523
Oil Age	hrs	Client Info		599	520	500
Oil Changed		Client Info		Changed	Changed	Changed
Sample Status				NORMAL	NORMAL	NORMAL

CONTAMINATION		method	limit/base	current	history1	history2
Fuel	WC Method	>5		<1.0	<1.0	<1.0
Water	WC Method	>0.2		NEG	NEG	NEG
Glycol	WC Method			NEG	NEG	NEG

WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>100	67	111	209
Chromium	ppm	ASTM D5185m	>20	2	3	5
Nickel	ppm	ASTM D5185m	>4	0	<1	<1
Titanium	ppm	ASTM D5185m		0	<1	<1
Silver	ppm	ASTM D5185m	>3	0	0	0
Aluminum	ppm	ASTM D5185m	>20	34	80	146
Lead	ppm	ASTM D5185m	>40	0	0	<1
Copper	ppm	ASTM D5185m	>330	5	20	128
Tin	ppm	ASTM D5185m	>15	0	<1	<1
Vanadium	ppm	ASTM D5185m		0	0	0
Cadmium	ppm	ASTM D5185m		0	0	0

ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		9	10	20
Barium	ppm	ASTM D5185m		0	0	5
Molybdenum	ppm	ASTM D5185m		60	50	50
Manganese	ppm	ASTM D5185m		1	3	8
Magnesium	ppm	ASTM D5185m		867	791	817
Calcium	ppm	ASTM D5185m		1454	1166	1271
Phosphorus	ppm	ASTM D5185m		941	799	703
Zinc	ppm	ASTM D5185m		1193	1031	967
Sulfur	ppm	ASTM D5185m		3283	2343	2542

CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	11	14	50
Sodium	ppm	ASTM D5185m		5	7	9
Potassium	ppm	ASTM D5185m	>20	67	209	298


INFRA-RED		method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844	>3	0.7	0.6	0.6
Nitration	Abs/cm	*ASTM D7624	>20	12.6	11.7	12.4
Sulfation	Abs/.1mm	*ASTM D7415	>30	25.7	23.7	24.2

FLUID DEGRADATION		method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414	>25	24.9	22.3	22.7
Base Number (BN)	mg KOH/g	ASTM D2896		5.7	6.1	5.0




OIL ANALYSIS REPORT


FT-IR (Direct Trend)




Aluminum (ppm)



Viscosity @ 100°C



Aluminum (ppm)




VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG


FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	11.9	11.6	13.3

GRAPHS


Ferrous Alloys




Non-ferrous Metals



Viscosity @ 100°C



Base Number



Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : SBP0007099 **Received** : 15 Jul 2024
Lab Number : 06237431 **Tested** : 16 Jul 2024
Unique Number : 11126265 **Diagnosed** : 16 Jul 2024 - Wes Davis
Test Package : FLEET

Constructors Inc. - 603659
 6500 N 70TH ST
 LINCOLN, NE
 US 68507
 Contact: Loren Michael
 LorenM@constructorslincoln.com
 T: (402)434-2157
 F:

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)