

## **OIL ANALYSIS REPORT**

Sample Rating Trend





Area

**MINING ME-024 CATERPILLAR 980 WFX01606 Diesel Engine** 

SHELL RIMULA SUPER SAE 15W40 (--- GAL)

## SAMPLE INFORMATION method limit/base current history1 history2 WC0934830 Sample Number **Client Info** No corrective action is recommended at this time. Sample Date Client Info 11 Jul 2024 Resample at the next service interval to monitor. Client Info 242 Machine Age hrs Oil Age hrs Client Info 242 Metal levels are typical for a new component Oil Changed **Client Info** Not Changd ABNORMAL Sample Status CONTAMINATION method limit/base current history1 history2 Light fuel dilution occurring. Elemental level of silicon (Si) above normal indicating ingress of seal >0.2 Water WC Method NEG Glycol WC Method NEG WEAR METALS method limit/base current historv1 history2 Fuel is present in the oil and is lowering the viscosity. The BN result indicates that there is Iron ASTM D5185m >100 28 ppm ASTM D5185m >20 Chromium ppm <1 Nickel ASTM D5185m >2 0 ppm ASTM D5185m >2 n Titanium ppm Silver ppm ASTM D5185m >2 0 Aluminum ASTM D5185m >25 3 ppm ASTM D5185m >40 4 Lead ppm ASTM D5185m Copper ppm >330 344 3 Tin ppm ASTM D5185m >15 Vanadium ASTM D5185m 0 ppm Cadmium ppm ASTM D5185m 0 **ADDITIVES** method limit/base current history1 history2 Boron ppm ASTM D5185m 35 Barium ppm ASTM D5185m 0 39 Molybdenum ppm ASTM D5185m 2 Manganese ppm ASTM D5185m 507 Magnesium ppm ASTM D5185m Calcium ASTM D5185m 2840 1610 ppm Phosphorus ppm ASTM D5185m 1150 854 Zinc ASTM D5185m 1270 1130 ppm Sulfur 2829 ppm ASTM D5185m 2795 **CONTAMINANTS** method limit/base current history1 history2 Silicon ASTM D5185m >25 90 ppm 2 Sodium ASTM D5185m ppm Potassium ASTM D5185m >20 2 ppm Fuel % ASTM D3524 >5 3.3 **INFRA-RED** method limit/base current history1 history2 0.2 % >3 Soot % \*ASTM D7844 Nitration Abs/cm \*ASTM D7624 >20 8.2 23.6 Sulfation \*ASTM D7415 >30 Abs/.1mm **FLUID DEGRADATION** method limit/base current history1 history2 >25 20.6 Oxidation Abs/.1mm \*ASTM D7414 Base Number (BN) mg KOH/g ASTM D2896 10.6 9.2

Recommendation

DIAGNOSIS

Wear

breaking in.

material.

Contamination

Fluid Condition

suitable alkalinity remaining in the oil.



## **OIL ANALYSIS REPORT**



Report Id: COVLUG [WUSCAR] 06237582 (Generated: 07/18/2024 09:43:29) Rev: 1

Submitted By: Chris Bowers

Page 2 of 2