

OIL ANALYSIS REPORT

Sample Rating Trend



Area SMART OIL Machine Io HERTZ VE032784 Component

Component Compressor

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition


The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

SAMPLE INFORM	NATION	method	limit/base	current	history1	history2
Sample Number		Client Info		UHK06237907	UHK06185111	
Sample Date		Client Info		04 Jun 2024	06 Mar 2024	
Machine Age	hrs	Client Info		1801	684	
Oil Age	hrs	Client Info		1801	684	
Oil Changed		Client Info		Not Changd	Not Changd	
Sample Status				NORMAL	NORMAL	
CONTAMINATIO	N	method	limit/base	current	history1	history2
Water		WC Method	>0.1	NEG	NEG	
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	4	2	
Chromium	ppm	ASTM D5185m	>10	0	<1	
Nickel	ppm	ASTM D5185m		0	0	
Titanium	ppm	ASTM D5185m		0	<1	
Silver	ppm	ASTM D5185m		0	<1	
Aluminum	ppm	ASTM D5185m	>25	5	3	
Lead	ppm	ASTM D5185m	>25	0	<1	
Copper	ppm	ASTM D5185m	>50	2	1	
Tin	ppm	ASTM D5185m	>15	0	<1	
Vanadium	ppm	ASTM D5185m		0	<1	
Cadmium	ppm	ASTM D5185m		0	0	
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0	0	
Barium	ppm	ASTM D5185m		0	0	
Molybdenum	ppm	ASTM D5185m		0	0	
Manganese	ppm	ASTM D5185m		0	0	
Magnesium	ppm	ASTM D5185m		<1	0	
Calcium	ppm	ASTM D5185m	20	0	0	
Phosphorus	ppm	ASTM D5185m		41	52	
Zinc	ppm	ASTM D5185m		0	0	
Sulfur	ppm	ASTM D5185m		462	476	
CONTAMINANTS	3	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	<1	1	
Sodium	ppm	ASTM D5185m		2	0	
Potassium	ppm	ASTM D5185m	>20	0	1	
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045		0.10	0.17	



44 42 Abnormal 40. Mar6/24

OIL ANALYSIS REPORT



	White Metal Yellow Metal	scalar	*Visual	NONE		NONE	
				NONE	NONE	NONE	
	Description	scalar	*Visual	NONE	NONE	NONE	
	Precipitate	scalar	*Visual	NONE	NONE	NONE	
	Silt	scalar	*Visual	NONE	NONE	NONE	
	Debris	scalar	*Visual	NONE	NONE	NONE	
	Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	
Jun4,24	Appearance	scalar	*Visual	NORML	NORML	NORML	
٦ ^ر	Odor	scalar	*Visual	NORML	NORML	NORML	
	Emulsified Water	scalar	*Visual	>0.1	NEG	NEG	
	Free Water	scalar	*Visual		NEG	NEG	
	FLUID PROPER	TIES	method	limit/base	current	history1	history2
	Visc @ 40°C	cSt	ASTM D445	46	45.9	46.7	
	SAMPLE IMAGE	S	method	limit/base	current	history1	history2
+∑,hnuL	Color						no image
	Bottom						no image
	GRAPHS Ferrous Alloys						
	Ferrous Alloys	ls		Jun4/24			
	Ferrous Alloys	ls		Jun424			
	Ferrous Alloys	ls		Jun4/24	Acid Number		
	Ferrous Alloys	ls		Jun4/24	Acid Number		
	Ferrous Alloys	ls		Jun4/24	Acid Number		
	Ferrous Alloys	ls		Jun4/24	Acid Number		
	Ferrous Alloys	Is		(0,H00, 0.15- 10,010,015- 0,10,010,015- 0,010,010,015- 0,010,015- 0,010,015- 0,010,010,010,010- 0,010,010,010,010- 0,010,010,010,010,010- 0,010,010,010,010,010,010,010,010,010,0	Acid Number		
	Ferrous Alloys	ls		Jun4/24	Acid Number		

Contact/Location: Service Manager - UCATLHER Page 2 of 2