


# **OIL ANALYSIS REPORT**

Sample Rating Trend



Machine Id

# KAESER AS20T 2324131 (S/N 1013)

Compressor

KAESER SIGMA (OEM) M-460 (--- QTS)

## **DIAGNOSIS**

#### Recommendation

Oil and filter change at the time of sampling has been noted. No corrective action is recommended at this time. Resample at the next service interval to monitor.

#### Wear

All component wear rates are normal.

## Contamination

There is a high amount of particulates present in the oil.

#### **Fluid Condition**

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

			Jul2013	Jul2024		
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		KCPA020771	KCP29720	
Sample Date		Client Info		09 Jul 2024	08 Jul 2013	
Machine Age	hrs	Client Info		71299	48704	
Oil Age	hrs	Client Info		2144	930	
Oil Changed		Client Info		Changed	N/A	
Sample Status				ABNORMAL	MARGINAL	
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	5	<1	
Chromium	ppm	ASTM D5185m	>10	0	0	
Nickel	ppm	ASTM D5185m		0	0	
Titanium	ppm	ASTM D5185m		0	0	
Silver	ppm	ASTM D5185m		0	0	
Aluminum	ppm	ASTM D5185m	>25	<1	0	
Lead	ppm	ASTM D5185m	>25	0	0	
Copper	ppm	ASTM D5185m	>50	3	16	
Tin	ppm	ASTM D5185m	>15	0	0	
Antimony	ppm	ASTM D5185m			0	
Vanadium	ppm	ASTM D5185m		0	0	
Cadmium	ppm	ASTM D5185m		0	<1	
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	0	0	0	
Barium	ppm	ASTM D5185m	90	0	0	
Molybdenum	ppm	ASTM D5185m	0	0	0	
Manganese	ppm	ASTM D5185m		0	0	
Magnesium	ppm	ASTM D5185m	100	31	0	
Calcium	ppm	ASTM D5185m	0	0	0	
Phosphorus	ppm	ASTM D5185m	0	0	0	
Zinc	ppm	ASTM D5185m	0	52	39	
Sulfur	ppm	ASTM D5185m	23500	23990	20590	
CONTAMINANTS	5	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	4	4	
Sodium	ppm	ASTM D5185m		6	<1	
Potassium	ppm	ASTM D5185m	>20	<1	6	
Water	%	ASTM D6304	>0.1	0.014	0.001	
ppm Water	ppm	ASTM D6304	>1000	146	10	
FLUID CLEANLIN	IESS	method	limit/base	current	history1	history2
Particles >4μm		ASTM D7647		63850	1102	
Particles >6µm		ASTM D7647	>1300	<u> </u>	600	
Particles >14μm		ASTM D7647	>80	<u>▲</u> 536	<u>102</u>	
Particles >21µm		ASTM D7647	>20	<u>^</u> 72	<u></u> 34	
Particles >38μm		ASTM D7647	>4	1	<u> 5</u>	
Particles >71µm		ASTM D7647	>3	0	0	
Oil Cleanliness		ISO 4406 (c)	>/17/13	<u>23/21/16</u>	<u> </u>	
FLUID DEGRADA	TION	method	limit/base	current	history1	history2



## OIL ANALYSIS REPORT







Certificate 12367

Laboratory Sample No.

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 : KCPA020771 Lab Number : 06238397 Unique Number : 11127231

Received : 16 Jul 2024 **Tested** : 17 Jul 2024

: 18 Jul 2024 - Don Baldridge Diagnosed

Test Package : IND 2 ( Additional Tests: KF, PrtCount ) To discuss this sample report, contact Customer Service at 1-800-237-1369.

 $^st$  - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T: F:

Contact/Location: ? ? - PRECOM

PRECISE CAST PROTOTYPES

7501 DAHLIA ST

US 80022

Contact:

COMMERCE CITY, CO