


OIL ANALYSIS REPORT

Sample Rating Trend



Machine Id

4893191 (S/N 1261)

Component Compressor

KAESER SIGMA (OEM) FG-460 (--- GAL)

DIAGNOSIS

Recommendation

No corrective action is recommended at this time. Oil and filter change at the time of sampling has been noted. Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is a high amount of particulates present in the oil.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

Aug2022 Jul2023 Jul2024						
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		KCPA020783	KCPA004794	KCP31957
Sample Date		Client Info		08 Jul 2024	28 Jul 2023	31 Aug 2022
Machine Age	hrs	Client Info		12001	9234	8572
Oil Age	hrs	Client Info		3000	0	3000
Oil Changed		Client Info		Changed	N/A	Changed
Sample Status				ABNORMAL	ABNORMAL	ABNORMAL
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	3	14	6
Chromium	ppm	ASTM D5185m	>10	0	0	0
Nickel	ppm	ASTM D5185m	>3	0	<1	0
Titanium	ppm	ASTM D5185m	>3	0	0	0
Silver	ppm	ASTM D5185m	>2	0	0	0
Aluminum	ppm	ASTM D5185m	>10	3	<u>^</u> 23	4
Lead	ppm	ASTM D5185m	>10	0	<1	0
Copper	ppm	ASTM D5185m	>50	<1	<1	1
Tin	ppm	ASTM D5185m	>10	<1	<1	0
Vanadium	ppm	ASTM D5185m		0	0	0
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0	0	0
Barium	ppm	ASTM D5185m		0	<1	0
Molybdenum	ppm	ASTM D5185m		0	0	0
Manganese	ppm	ASTM D5185m		0	<1	0
Magnesium	ppm	ASTM D5185m		1	3	0
Calcium	ppm	ASTM D5185m		0	0	0
Phosphorus	ppm	ASTM D5185m	500	288	553	283
Zinc	ppm	ASTM D5185m		309	551	323
Sulfur	ppm	ASTM D5185m		1916	2341	2302
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	<1	<1	0
Sodium	ppm	ASTM D5185m		<1	3	<1
Potassium	ppm	ASTM D5185m	>20	0	1	0
Water	%	ASTM D6304	>0.05	0.004	0.011	0.00
ppm Water	ppm	ASTM D6304	>500	46	117.7	0.00
FLUID CLEANLIN	IESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647		19923	9159	31459
Particles >6µm		ASTM D7647	>1300	<u> </u>	▲ 3427	<u>▲</u> 13215
Particles >14μm		ASTM D7647	>80	2850	△ 310	<u>2335</u>
Particles >21µm		ASTM D7647	>20	<u>^</u> 905	<u>^</u> 73	<u>415</u>
Particles >38μm		ASTM D7647	>4	<u>^</u> 25	3	<u> </u>
Particles >71μm		ASTM D7647	>3	1	1	0
Oil Cleanliness		ISO 4406 (c)	>/17/13	<u> </u>	<u>^</u> 20/19/15	<u>22/21/18</u>
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045	1.5	0.67	1.098	0.79



OIL ANALYSIS REPORT







Certificate 12367

Laboratory Sample No. Lab Number

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 : KCPA020783 : 06238417 Unique Number : 11127251

Received : 16 Jul 2024 Tested Diagnosed

: 17 Jul 2024 : 18 Jul 2024 - Don Baldridge

Test Package : IND 2 (Additional Tests: KF, PrtCount) To discuss this sample report, contact Customer Service at 1-800-237-1369.

 st - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

WATERFORD ALMOND HULLER

12013 EL POMAR AVE WATERFORD, CA US 95386

Contact: JANELLE

janelle@riddlerranchesinc.com T:

Report Id: WATWATCAL [WUSCAR] 06238417 (Generated: 07/18/2024 12:50:39) Rev: 1

Contact/Location: JANELLE ? - WATWATCAL

F: