

# OIL ANALYSIS REPORT

# VOLVO PENTA

501 Madison Avenue  
Cary, NC 27513  
USA  
1-800-237-1369  
(919) 379-4102  
Fax (919) 379-4050

C8-1175 Appleby Line  
Burlington, ON L7L 5H9  
CANADA  
1-800-268-2131  
(905) 569-8600  
Fax (905) 569-8605

**VOLVOPENTA** sample kits will be replaced with unused kits if defective in manufacture, labeling, or packaging, or if lost by us or any associate company even though by negligence or other fault.

**VOLVOPENTA** shall not be liable or responsible for the future performance or failure of any engine, piece of equipment or material involved in any test or sample. The Company makes no warranties, representations, or guaranties with respect to the performance of any such engine, piece of equipment, or material.

**NOTE 1:** For sample identification, please ensure that you either print labels and place on the sample bottle or that you label the sample cap with the reference number (\*Label) shown below.

**NOTE 2:** Please attach 1 Sample Information Forms (SIFs) as proof of payment for these analysis.

## Shipping Info

Shipped Via:  
Tracking Number:  
Shipped On:  
Submitted By:

## Machine / Sample Info

Make: JOHN DEERE  
Machine ID: JOHN DEERE RG6135L040310  
Machine Hrs: 414.0  
Sample Date: 06/07/2023

## Customer

Bay Marine Boatworks Inc.  
310 West Cutting Blvd.  
RICHMOND, CA 94804 US  
Attn: David Vandervoort  
Ph: (510)237-0140 Fax:

*Label	Component	Time on Oil	Oil Maint	Filter Maint	Oil Type
not sampled	Port Diesel Engine	194.0	Not Changd	Not Changd	JOHN DEERE ENGINE OIL PLUS 50 II 15W40

For best results we suggest the following precautions when taking the sample.

**INSTRUCTIONS FOR TAKING SAMPLE** - the SAMPLE should not be taken MORE THAN 30 MINUTES after shutdown, and the oil should have been in service for at least 10 hours or 500 miles, before the oil can accurately reflect wear conditions. AVOID CONTAMINATION OF THE SAMPLE - Clean around the drain plug before draining. Remove the drain, and when about half the oil has run out, catch the sample by inserting the bottle into the oil stream. The bottle should be at least 3/4 filled. Do not remove the bottle cap until you are ready to take the sample, and recap the bottle immediately after filling. Take care not to confuse samples from different units. Or, remove sample with a suction pump by inserting the siphon tube down the dipstick tube or into the sump/reservoir. The siphon tube must be clean by either replacement or rinsing with a solvent and drying. Do not rinse with gasoline or diesel fuel. Or, Engines with sample ports (i.e. gauge plugs, probalizer mini-plugs), follow the specific instructions pertaining to the sampling device purchased.