

501 Madison Avenue  
 Cary, NC 27513  
 USA  
 1-800-237-1369  
 (919) 379-4102  
 Fax (919) 379-4050

C8-1175 Appleby Line  
 Burlington, ON L7L 5H9  
 CANADA  
 1-800-268-2131  
 (905) 569-8600  
 Fax (905) 569-8605

**DEFAULT** sample kits will be replaced with unused kits if defective in manufacture, labeling, or packaging, or if lost by us or any associate company even though by negligence or other fault.

**DEFAULT** shall not be liable or responsible for the future performance or failure of any engine, piece of equipment or material involved in any test or sample. The Company makes no warranties, representations, or guaranties with respect to the performance of any such engine, piece of equipment, or material.

**NOTE 1:** For sample identification, please ensure that you either print labels and place on the sample bottle or that you label the sample cap with the reference number (\*Label) shown below.

**NOTE 2:** Please attach 3 Sample Information Forms (SIFs) as proof of payment for these analysis.

**Shipping Info**

Shipped Via:  
 Tracking Number:  
 Shipped On:  
 Submitted By:

**Machine / Sample Info**

Make: LIEBHERR  
 Machine ID: LIEBHERR TA 230 145963-1513  
 Machine Hrs: 419.0  
 Sample Date: 06/22/2023

**Customer**

NUECES POWER EQUIPMENT  
 7667 N SAM HOUSTON PKWY EAST  
 HUMBLE, TX 77396 US  
 Attn: SARKES GONZALEZ  
 Ph: (713)247-0066 Fax:

*Label	Component	Time on Oil	Oil Maint	Filter Maint	Oil Type
not sampled	Diesel Engine				
not sampled	Transmission				
not sampled	Hydraulic System				
not sampled	Front Axle				
not sampled	Center Differential	419.0			LIEBHERR GEAR MF 80W
not sampled	Bogie/Center Axle				
not sampled	1 Differential	419.0			LIEBHERR GEAR MF 80W
not sampled	Rear Differential	419.0			LIEBHERR GEAR MF 80W
not sampled	Rear Axle				

For best results we suggest the following precautions when taking the sample.

**INSTRUCTIONS FOR TAKING SAMPLE** - the SAMPLE should not be taken MORE THAN 30 MINUTES after shutdown, and the oil should have been in service for at least 10 hours or 500 miles, before the oil can accurately reflect wear conditions.  
 AVOID CONTAMINATION OF THE SAMPLE - Clean around the drain plug before draining. Remove the drain, and when about half the oil has run out, catch the sample by inserting the bottle into the oil stream. The bottle should be at least 3/4 filled.  
 Do not remove the bottle cap until you are ready to take the sample, and recap the bottle immediately after filling. Take care not to confuse samples from different units,  
 Or, remove sample with a suction pump by inserting the siphon tube down the dipstick tube or into the sump/reservoir. The siphon tube must be clean by either replacement or rinsing with a solvent and drying. Do not rinse with gasoline or diesel fuel.  
 Or, Engines with sample ports (i.e. gauge plugs, probalizer mini-plugs), follow the specific instructions pertaining to the sampling device purchased.