



# SAMPLE SUBMISSION FORM

## Oil Analysis Laboratories

501 Madison Avenue C8-1175 Appleby Line  
 Cary, NC 27513 Burlington, ON L7L 5H9  
 USA CANADA  
 1-800-237-1369 1-800-268-2131  
 (919) 379-4102 (905) 569-8600  
 Fax (919) 379-4050 Fax (905) 569-8605

WEARCHECK sample kits will be replaced with unused kits if defective in manufacture, labeling, or packaging, or if lost by us or any associate company even though by negligence or other fault.

WEARCHECK shall not be liable or responsible for the future performance or failure of any engine, piece of equipment or material involved in any test or sample. The Company makes no warranties, representations, or guaranties with respect to the performance of any such engine, piece of equipment, or material.

**NOTE 1:** For sample identification, please ensure that you either print labels and place on the sample bottle or that you label the sample cap with the reference number (\*Label) shown below.

**NOTE 2:** Please attach 6 Sample Information Forms (SIFs) as proof of payment for these analysis.







**Shipping Info**

Shipped Via:  
 Tracking Number:  
 Shipped On:  
 Submitted By: BILL BUTLER [Oil Filtration Solutions Ltd.]

### SAMPLING INSTRUCTIONS AND PRECAUTIONS

For best results we suggest the following precautions when taking the sample.  
**INSTRUCTIONS FOR TAKING SAMPLE** - the SAMPLE should not be taken MORE THAN 30 MINUTES after shutdown, and the oil should have been in service for at least 10 hours or 500 miles, before the oil can accurately reflect wear conditions.  
**AVOID CONTAMINATION OF THE SAMPLE** - Clean around the drain plug before draining. Remove the drain, and when about half the oil has run out, catch the sample by inserting the bottle into the oil stream. The bottle should be at least 3/4 filled. Do not remove the bottle cap until you are ready to take the sample, and recap the bottle immediately after filling. Take care not to confuse samples from different units.  
 Or, remove sample with a suction pump by inserting the siphon tube down the dipstick tube or into the sump/reservoir. The siphon tube must be clean by either replacement or rinsing with a solvent and drying. Do not rinse with gasoline or diesel fuel.  
 Or, Engines with sample ports (i.e. gauge plugs, probalizer mini-plugs), follow the specific instructions pertaining to the sampling device purchased.

**Oil Filtration Solutions Ltd.**

	*Label : 398243 Sample Number : OF0000299 Test Package : MOB 1 Sample Date : 09/15/2023	Area : McCarthy's Fisheries Ltd Machine Id : COMMERCIAL FISHING MV Executioner Component : JOHN DEERE 4045DFM70 PE4045D984893 1 Genset Fluid : (18 LTR)	Machine Age : Fluid Age : 260.0 Filter Age : 260.0 Fluid Maintenance : Changed Filter Maintenance : Changed
	*Label : 398244 Sample Number : OF0000306 Test Package : MOB 1 Sample Date : 09/15/2023	Area : McCarthy's Fisheries Ltd Machine Id : COMMERCIAL FISHING MV Executioner Component : JOHN DEERE 6068TFM76 PE6068T97568 2 Genset Fluid : (22 LTR)	Machine Age : Fluid Age : 204.0 Filter Age : 204.0 Fluid Maintenance : Changed Filter Maintenance : Changed
	*Label : 398245 Sample Number : OF0000307 Test Package : MOB 1 Sample Date : 09/15/2023	Area : McCarthy's Fisheries Ltd Machine Id : COMMERCIAL FISHING MV Executioner Component : JOHN DEERE 6068AFM85 PE6068N020429 3 Genset Fluid : (22 LTR)	Machine Age : Fluid Age : 183.0 Filter Age : 183.0 Fluid Maintenance : Changed Filter Maintenance : Changed
	*Label : 398246 Sample Number : OF0000305 Test Package : MOB 2 Sample Date : 09/15/2023	Area : McCarthy's Fisheries Ltd Machine Id : COMMERCIAL FISHING MV Executioner Component : CATERPILLAR C-12 NFL05091 4 Genset Fluid : PETRO CANADA DURON MOTOR OIL SAE 30 (45 LTR)	Machine Age : Fluid Age : 192.0 Filter Age : 192.0 Fluid Maintenance : Changed Filter Maintenance : Changed
	*Label : 398247 Sample Number : OF0000304 Test Package : MOB 1 Sample Date : 09/15/2023	Area : McCarthy's Fisheries Ltd Machine Id : COMMERCIAL FISHING MV Executioner Component : YANMAR 6EY17W EY17A Main Engine Fluid : (1200 LTR)	Machine Age : Fluid Age : 460.0 Filter Age : 450.0 Fluid Maintenance : Not Changed Filter Maintenance : Changed
	*Label : 398248 Sample Number : OF0000300 Test Package : MOB 1 Sample Date : 09/15/2023	Area : McCarthy's Fisheries Ltd Machine Id : COMMERCIAL FISHING MV Executioner Component : MVET Transmission Fluid : (45 LTR)	Machine Age : Fluid Age : Filter Age : Fluid Maintenance : Not Changed Filter Maintenance :