



SAMPLE SUBMISSION FORM

Oil Analysis Laboratories

501 Madison Avenue C8-1175 Appleby Line
 Cary, NC 27513 Burlington, ON L7L 5H9
 USA CANADA
 1-800-237-1369 1-800-268-2131
 (919) 379-4102 (905) 569-8600
 Fax (919) 379-4050 Fax (905) 569-8605

WEARCHECK sample kits will be replaced with unused kits if defective in manufacture, labeling, or packaging, or if lost by us or any associate company even though by negligence or other fault.

WEARCHECK shall not be liable or responsible for the future performance or failure of any engine, piece of equipment or material involved in any test or sample. The Company makes no warranties, representations, or guaranties with respect to the performance of any such engine, piece of equipment, or material.

NOTE 1: For sample identification, please ensure that you either print labels and place on the sample bottle or that you label the sample cap with the reference number (*Label) shown below.

NOTE 2: Please attach 5 Sample Information Forms (SIFs) as proof of payment for these analysis.

Shipping Info

Shipped Via: Sameday
 Tracking Number: SSJ00860841
 Shipped On: 09/26/2023
 Submitted By: BILL BUTLER [Oil Filtration Solutions Ltd.]

SAMPLING INSTRUCTIONS AND PRECAUTIONS

For best results we suggest the following precautions when taking the sample.

INSTRUCTIONS FOR TAKING SAMPLE - the SAMPLE should not be taken MORE THAN 30 MINUTES after shutdown, and the oil should have been in service for at least 10 hours or 500 miles, before the oil can accurately reflect wear conditions.
AVOID CONTAMINATION OF THE SAMPLE - Clean around the drain plug before draining. Remove the drain, and when about half the oil has run out, catch the sample by inserting the bottle into the oil stream. The bottle should be at least 3/4 filled. Do not remove the bottle cap until you are ready to take the sample, and recap the bottle immediately after filling. Take care not to confuse samples from different units.
 Or, remove sample with a suction pump by inserting the siphon tube down the dipstick tube or into the sump/reservoir. The siphon tube must be clean by either replacement or rinsing with a solvent and drying. Do not rinse with gasoline or diesel fuel.
 Or, Engines with sample ports (i.e. gauge plugs, probalizer mini-plugs), follow the specific instructions pertaining to the sampling device purchased.

Oil Filtration Solutions Ltd.

	*Label : 398269	Area	OLIVIC FISHERIES LTD	Machine Age	: 7355.0
	Sample Number : OF0000752	Machine Id	FISHING VESSEL MV NEWFOUNDLAND MARINER	Fluid Age	: 278.0
	Test Package : MOB 1	Component	Nanni Diesel QM533M60 GDK16070077 1 Genset	Filter Age	: 287.0
	Sample Date : 03/22/2023	Fluid	(8 LTR)	Fluid Maintenance	: Changed
				Filter Maintenance	: Changed
	*Label : 398270	Area	OLIVIC FISHERIES LTD	Machine Age	: 22.0
	Sample Number : OF0000753	Machine Id	FISHING VESSEL MV NEWFOUNDLAND MARINER	Fluid Age	: 22.0
	Test Package : MOB 1	Component	JOHN DEERE 6068TFM50 CD6068TZ5058 2 Genset	Filter Age	: 22.0
	Sample Date : 03/22/2023	Fluid	(10 LTR)	Fluid Maintenance	: Changed
				Filter Maintenance	: Changed
	*Label : 398271	Area	OLIVIC FISHERIES LTD	Machine Age	: 5200.0
	Sample Number : OF0000709	Machine Id	FISHING VESSEL MV NEWFOUNDLAND MARINER	Fluid Age	: 700.0
	Test Package : MOB 1	Component	MVNMHS Hydraulic System	Filter Age	: 700.0
	Sample Date : 03/22/2023	Fluid	(2000 LTR)	Fluid Maintenance	: Changed
				Filter Maintenance	: Changed
	*Label : 398272	Area	OLIVIC FISHERIES LTD	Machine Age	: 13974.0
	Sample Number : OF0000751	Machine Id	FISHING VESSEL MV NEWFOUNDLAND MARINER	Fluid Age	: 537.0
	Test Package : MOB 1	Component	MITSUBISHI S12A2-Y1MPTA 27481 Main Engine	Filter Age	: 537.0
	Sample Date : 03/22/2023	Fluid	(144 LTR)	Fluid Maintenance	: Changed
				Filter Maintenance	: Changed
	*Label : 398273	Area	OLIVIC FISHERIES LTD	Machine Age	: 13971.0
	Sample Number : OF0000710	Machine Id	FISHING VESSEL MV NEWFOUNDLAND MARINER	Fluid Age	: 1240.0
	Test Package : MOB 1	Component	TWIN DISC MVNMT Transmission	Filter Age	: 1240.0
	Sample Date : 03/22/2023	Fluid	(38 LTR)	Fluid Maintenance	: Changed
				Filter Maintenance	: Changed