

## SAMPLE SUBMISSION FORM

**Oil Analysis Laboratories** 

501 Madison Avenue Cary, NC 27513 USA 1-800-237-1369 (919) 379-4102 Fax (919) 379-4050 C8-1175 Appleby Line Burlington, ON L7L 5H9 CANADA 1-800-268-2131 (905) 569-8600 Fax (905) 569-8605

**NOTE 1:** For sample identification, please ensure that you either print labels and place on the sample bottle <u>or</u> that you label the sample cap with the reference number (\*Label) shown below.

**NOTE 2:** Please attach 6 Sample Information Forms (SIFs) as proof of payment for these analysis.

WEARCHECK sample kits will be replaced with unused kits if defective in manufacture, labeling, or packaging, or if lost by us or any associate company even though by negligence or other fault.

WEARCHECK shall not be liable or responsible for the future performance or failure of any engine, piece of equipment or material involved in any test or sample. The Company makes no warranties, representations, or guaranties with respect to the performance of any such engine, piece of equipment, or material.

## Shipping Info

Shipped Via: Purolator Tracking Number: 15389148576 Shipped On: 10/16/2023 Submitted By: BILL BUTLER [Oil Filtration Solutions Ltd.]

SAMPLING INSTRUCTIONS AND PRECAUTIONS

For best results we suggest the following precautions when taking the sample. **INSTRUCTIONS FOR TAKING SAMPLE** - the SAMPLE should not be taken MORE THAN 30 MINUTES after shutdown, and the oil should have been in service for at least 10 hours or 500 miles, before the oil can accurately reflect wear conditions. AVOID CONTAMINATION OF THE SAMPLE - Clean around the drain plug before draining. Remove the drain, and when about half the oil has run out, catch the sample by inserting the bottle into the oil stream. The bottle should be at least 3/4 filled. Do not remove the bottle cap untiliy ou are ready to take the sample, and recap the bottle immediately after filling. Take care not to confuse samples from different units,

Or, remove sample with a suction pump by inserting the siphon tube down the dipstick tube or into the sump/reservoir. The siphon tube must be clean by either replacement or rinsing with a solvent and drying. Do not rinse with gasoline or diesel fuel. Or, Engines with sample ports (i.e. gauge plugs, probalizer mini-plugs), follow the specific instructions pertaining to the sampling device purchased.

Oil Filtration Solutions Ltd.	
-------------------------------	--

*Label Sample Number Test Package Sample Date	: 405544 : OF0001019 : MOB 2 : 10/07/2023	Area Machine Id Component Fluid	R&M FISHERIES LTD FISHING VESSEL MV OCEAN TRAVELLER KUBOTA V3300 1J427-10000 1 Genset TOTAL FINA RUBIA TIR 7900 15W40 (9 LTR)	Machine Age Fluid Age Filter Age Fluid Maintenance Filter Maintenance	: 789.0 : 789.0 : 789.0 : Changed : Changed
*Label Sample Number Test Package Sample Date	: 405545 : OF0001018 : MOB 2 : 10/07/2023	Area Machine Id Component Fluid	R&M FISHERIES LTD FISHING VESSEL MV OCEAN TRAVELLER CATERPILLAR 3406 MVOTG2 2 Genset TOTAL FINA RUBIA TIR 7900 15W40 (20 LTR)	Machine Age Fluid Age Filter Age Fluid Maintenance Filter Maintenance	: 12730.0 : 720.0 : 720.0 : Changed : Changed
*Label Sample Number Test Package Sample Date	: 405546 : OF0001017 : MOB 2 : 10/07/2023	Area Machine Id Component Fluid	R&M FISHERIES LTD FISHING VESSEL MV OCEAN TRAVELLER CATERPILLAR 3406 MVOTG3 3 Genset TOTAL FINA RUBIA TIR 7900 15W40 (20 LTR)	Machine Age Fluid Age Filter Age Fluid Maintenance Filter Maintenance	: 36440.0 : 180.0 : 180.0 : Not Changd : Not Changd
*Label Sample Number	: 405547 : OF0001020	Area Machine Id	R&M FISHERIES LTD FISHING VESSEL MV OCEAN TRAVELLER	Machine Age Fluid Age Filter Age	: 5256.0 : 756.0 : 156.0
Test Package Sample Date	: MOB 2 : 10/07/2023	Component Fluid	MVOTHS Hydraulic System TOTAL FINA NEVASTANE FG AW 32 (2500 LTR)	Fluid Maintenance Filter Maintenance	: Not Changd : Not Changd
	-	1		Fluid Maintenance	: Not Changd