

## SAMPLE SUBMISSION FORM

Oil Analysis Laboratories

501 Madison Avenue Cary, NC 27513 USA

C8-1175 Appleby Line Burlington, ON L7L 5H9 **CANADA** 1-800-268-2131

1-800-237-1369 (919) 379-4102 Fax (919) 379-4050

(905) 569-8600 Fax (905) 569-8605

NOTE 1: For sample identification, please ensure that you either print labels and place on the sample bottle or that you label the sample cap with the reference number (\*Label) shown below.

NOTE 2: Please attach 6 Sample Information Forms (SIFs) as proof of payment for these analysis.

WEARCHECK sample kits will be replaced with unused kits if defective in manufacture, labeling, or packaging, or if lost by us or any associate company even though by negligence or other fault.

WEARCHECK shall not be liable or responsible for the future performance or failure of any engine, piece of equipment or material involved in any test or sample. The Company makes no warranties, representations, or guaranties with respect to the performance of any such engine, piece of equipment, or material.

## **Shipping Info**

Shipped Via:

Tracking Number:

Shipped On:

Submitted By: BILL BUTLER [Oil Filtration Solutions Ltd.]

SAMPLING INSTRUCTIONS AND PRECAUTIONS

For best results we suggest the following precautions when taking the sample.

INSTRUCTIONS FOR TAKING SAMPLE - the SAMPLE should not be taken MORE THAN 30 MINUTES after shutdown, and the oil should have been in service for at least 10 hours or 500 miles, before the oil can accurately reflect wear conditions. AVOID CONTAMINATION OF THE SAMPLE - Clean around the drain plug before draining. Remove the drain, and when about half the oil has run out, catch the sample by inserting the bottle into the oil stream. The bottle should be at least 3/4 filled. Do not remove the bottle cap until you are ready to take the sample, and recap the bottle immediately after filling. Take care not to confuse samples from different units,

Or, remove sample with a suction pump by inserting the siphon tube down the dipstick tube or into the sump/reservoir. The siphon tube must be clean by either replacement or rinsing with a solvent and drying. Do not rinse with gasoline or diesel fuel. Or, Engines with sample ports (i.e. gauge plugs, probalizer mini-plugs), follow the specific instructions pertaining to the sampling device purchased.

## Oil Filtration Solutions Ltd.

Label ample Number est Package ample Date	: 415097 : OF0000951 : MOB 2 : 11/01/2023	Area Machine Id Component Fluid	Y & J FISHERIES LTD FISHING VESSEL MV LASTING TRADITION KUBOTA V3300 4G1143 1 Genset PETRO CANADA DURON HP 15W40 (20 LTR)	Machine Age Fluid Age Filter Age Fluid Maintenance Filter Maintenance	: 21855.0 : 1151.0 : 1151.0 : Changed : Changed
Label ample Number est Package ample Date	: 415098 : OF0000958 : MOB 2 : 11/01/2023	Area Machine Id Component Fluid	Y & J FISHERIES LTD FISHING VESSEL MV LASTING TRADITION KUBOTA V3300 4G1632 2 Genset PETRO CANADA DURON HP 15W40 (20 LTR)	Machine Age Fluid Age Filter Age Fluid Maintenance Filter Maintenance	: 19462.0 : 1250.0 : 1250.0 : Changed : Changed
Label ample Number est Package ample Date	: 415099 : OF0000953 : MOB 2 : 11/01/2023	Area Machine Id Component Fluid	Y & J FISHERIES LTD FISHING VESSEL MV LASTING TRADITION JOHN DEERE 6068TFM50 CD6068T750551 3 Genset PETRO CANADA DURON HP 15W40 (30 LTR)	Machine Age Fluid Age Filter Age Fluid Maintenance Filter Maintenance	: 8182.0 : 1657.0 : 1657.0 : Changed : Changed
Label ample Number est Package	: 415100 : OF0000950 : MOB 2	Area Machine Id Component	Y & J FISHERIES LTD FISHING VESSEL MV LASTING TRADITION MVLTHS Hydraulic System	Machine Age Fluid Age Filter Age	: 8182.0 : 6185.0 : 657.0
Sample Date	: 11/01/2023	Fluid	AW HYDRAULIC OIL ISO 32 (1400 LTR)	Fluid Maintenance Filter Maintenance	: Not Changd : Changed
•	_	•	,		· ·

Transit Id: 415097 to 415102 Page 1 of 1