



SAMPLE SUBMISSION FORM

Oil Analysis Laboratories

501 Madison Avenue C8-1175 Appleby Line
 Cary, NC 27513 Burlington, ON L7L 5H9
 USA CANADA
 1-800-237-1369 1-800-268-2131
 (919) 379-4102 (905) 569-8600
 Fax (919) 379-4050 Fax (905) 569-8605

WEARCHECK sample kits will be replaced with unused kits if defective in manufacture, labeling, or packaging, or if lost by us or any associate company even though by negligence or other fault.

WEARCHECK shall not be liable or responsible for the future performance or failure of any engine, piece of equipment or material involved in any test or sample. The Company makes no warranties, representations, or guaranties with respect to the performance of any such engine, piece of equipment, or material.

NOTE 1: For sample identification, please ensure that you either print labels and place on the sample bottle or that you label the sample cap with the reference number (*Label) shown below.

NOTE 2: Please attach 5 Sample Information Forms (SIFs) as proof of payment for these analysis.

Shipping Info

Shipped Via:
 Tracking Number:
 Shipped On:
 Submitted By: LUIS FERNANDEZ [IKO HAGERSTOWN]

SAMPLING INSTRUCTIONS AND PRECAUTIONS

For best results we suggest the following precautions when taking the sample.

INSTRUCTIONS FOR TAKING SAMPLE - the SAMPLE should not be taken MORE THAN 30 MINUTES after shutdown, and the oil should have been in service for at least 10 hours or 500 miles, before the oil can accurately reflect wear conditions.
AVOID CONTAMINATION OF THE SAMPLE - Clean around the drain plug before draining. Remove the drain, and when about half the oil has run out, catch the sample by inserting the bottle into the oil stream. The bottle should be at least 3/4 filled. Do not remove the bottle cap until you are ready to take the sample, and recap the bottle immediately after filling. Take care not to confuse samples from different units.
 Or, remove sample with a suction pump by inserting the siphon tube down the dipstick tube or into the sump/reservoir. The siphon tube must be clean by either replacement or rinsing with a solvent and drying. Do not rinse with gasoline or diesel fuel.
 Or, Engines with sample ports (i.e. gauge plugs, probalizer mini-plugs), follow the specific instructions pertaining to the sampling device purchased.

IKO HAGERSTOWN

	*Label : 397395	Area	TPO - Extrusion	Machine Age : 3.0
	Sample Number : PCA0106223	Machine Id	Bottom Extruder Melt Pumps T3203	Fluid Age : 3.0
	Test Package : MOB 1	Component	Gearbox	Filter Age :
	Sample Date : 09/20/2023	Fluid	(14 GAL)	Fluid Maintenance : Not Changd
				Filter Maintenance :
	*Label : 397380	Area	TPO - Extrusion	Machine Age : 3.0
	Sample Number : PCA0106222	Machine Id	BOTTOM EXTRUDER T3198	Fluid Age : 3.0
	Test Package : MOB 1	Component	Bottom Gearbox	Filter Age :
	Sample Date : 09/20/2023	Fluid	(132 GAL)	Fluid Maintenance : Not Changd
				Filter Maintenance :
	*Label : 397384	Area	TPO - Extrusion Calender Hydraulic	Machine Age : 3.0
	Sample Number : PCA0106225	Machine Id	CALENDER ROLL T3320 (S/N 75063215)	Fluid Age : 3.0
	Test Package : MOB 1	Component	Hydraulic System	Filter Age :
	Sample Date : 09/20/2023	Fluid	(200 LTR)	Fluid Maintenance : Not Changd
				Filter Maintenance :
	*Label : 397397	Area	TPO - Extrusion	Machine Age : 3.0
	Sample Number : PCA0106224	Machine Id	Top Extruder Melt Pumps T3288	Fluid Age : 3.0
	Test Package : MOB 1	Component	Gearbox	Filter Age :
	Sample Date : 09/20/2023	Fluid	(14 GAL)	Fluid Maintenance : Not Changd
				Filter Maintenance :
	*Label : 397381	Area	TPO - Extrusion	Machine Age : 3.0
	Sample Number : PCA0106221	Machine Id	TOP EXTRUDER T3285	Fluid Age : 3.0
	Test Package : MOB 1	Component	Top Gearbox	Filter Age :
	Sample Date : 09/20/2023	Fluid	(132 GAL)	Fluid Maintenance : Not Changd
				Filter Maintenance :