



# SAMPLE SUBMISSION FORM

## Oil Analysis Laboratories

501 Madison Avenue	C8-1175 Appleby Line
Cary, NC 27513	Burlington, ON L7L 5H9
USA	CANADA
1-800-237-1369	1-800-268-2131
(919) 379-4102	(905) 569-8600
Fax (919) 379-4050	Fax (905) 569-8605

WEARCHECK sample kits will be replaced with unused kits if defective in manufacture, labeling, or packaging, or if lost by us or any associate company even though by negligence or other fault.

WEARCHECK shall not be liable or responsible for the future performance or failure of any engine, piece of equipment or material involved in any test or sample. The Company makes no warranties, representations, or guaranties with respect to the performance of any such engine, piece of equipment, or material.

**NOTE 1:** For sample identification, please ensure that you either print labels and place on the sample bottle or that you label the sample cap with the reference number (\*Label) shown below.

**NOTE 2:** Please attach 3 Sample Information Forms (SIFs) as proof of payment for these analysis.

### Shipping Info

Shipped Via:  
 Tracking Number:  
 Shipped On:  
 Submitted By: BOBBY LUCKY [WARRIOR TRACTOR AND EQUIPMENT - HUN]

### SAMPLING INSTRUCTIONS AND PRECAUTIONS

For best results we suggest the following precautions when taking the sample.

**INSTRUCTIONS FOR TAKING SAMPLE** - the SAMPLE should not be taken MORE THAN 30 MINUTES after shutdown, and the oil should have been in service for at least 10 hours or 500 miles, before the oil can accurately reflect wear conditions. **AVOID CONTAMINATION OF THE SAMPLE** - Clean around the drain plug before draining. Remove the drain, and when about half the oil has run out, catch the sample by inserting the bottle into the oil stream. The bottle should be at least 3/4 filled. Do not remove the bottle cap until you are ready to take the sample, and recap the bottle immediately after filling. Take care not to confuse samples from different units. Or, remove sample with a suction pump by inserting the siphon tube down the dipstick tube or into the sump/reservoir. The siphon tube must be clean by either replacement or rinsing with a solvent and drying. Do not rinse with gasoline or diesel fuel. Or, Engines with sample ports (i.e. gauge plugs, probalizer mini-plugs), follow the specific instructions pertaining to the sampling device purchased.

### WARRIOR TRACTOR AND EQUIPMENT - HUNTSVILLE

	*Label : 373457	Area	LAMBERT CONTRACTING	Machine Age : 510.0
	Sample Number : WE0004827	Machine Id	JOHN DEERE 470P 1FF470PAKNF000111	Fluid Age : 510.0
	Test Package : MOB 1	Component	JOHN DEERE 470P Right Swing Drive	Filter Age :
	Sample Date : 07/06/2023	Fluid	(2 GAL)	Fluid Maintenance : Not Changd
<hr/>				
	*Label : 373460	Area	LAMBERT CONTRACTING	Machine Age : 510.0
	Sample Number : WE0004823	Machine Id	JOHN DEERE 470P 1FF470PAKNF000111	Fluid Age : 510.0
	Test Package : MOB 1	Component	JOHN DEERE Tank Hydraulic System	Filter Age : 510.0
	Sample Date : 07/06/2023	Fluid	(82 GAL)	Fluid Maintenance : Not Changd
<hr/>				
	*Label : 360729	Machine Id	JOHN DEERE 748L 1DW748LBCNP715227	Machine Age : 1532.0
	Sample Number : WE0003527	Component	JOHN DEERE 748L Front Differential	Fluid Age : 1532.0
	Test Package : CONST	Fluid	JOHN DEERE HY-GARD HYD/TRANS (28 GAL)	Filter Age : 1532.0
	Sample Date : 06/06/2023			Fluid Maintenance : N/A
				Filter Maintenance : None