



SAMPLE SUBMISSION FORM

Oil Analysis Laboratories

| | |
|---|--|
| 501 Madison Avenue Cary, NC 27513 USA 1-800-237-1369 (919) 379-4102 Fax (919) 379-4050 | C8-1175 Appleby Line Burlington, ON L7L 5H9 CANADA 1-800-268-2131 (905) 569-8600 Fax (905) 569-8605 |
|---|--|

WEARCHECK sample kits will be replaced with unused kits if defective in manufacture, labeling, or packaging, or if lost by us or any associate company even though by negligence or other fault.

WEARCHECK shall not be liable or responsible for the future performance or failure of any engine, piece of equipment or material involved in any test or sample. The Company makes no warranties, representations, or guaranties with respect to the performance of any such engine, piece of equipment, or material.

NOTE 1: For sample identification, please ensure that you either print labels and place on the sample bottle or that you label the sample cap with the reference number (*Label) shown below.

NOTE 2: Please attach 11 Sample Information Forms (SIFs) as proof of payment for these analysis.







Shipping Info

Shipped Via:
Tracking Number:
Shipped On:
Submitted By: BOBBY LUCKY [WARRIOR TRACTOR AND EQUIPMENT - HUN]

SAMPLING INSTRUCTIONS AND PRECAUTIONS

For best results we suggest the following precautions when taking the sample.
INSTRUCTIONS FOR TAKING SAMPLE - the SAMPLE should not be taken MORE THAN 30 MINUTES after shutdown, and the oil should have been in service for at least 10 hours or 500 miles, before the oil can accurately reflect wear conditions.
AVOID CONTAMINATION OF THE SAMPLE - Clean around the drain plug before draining. Remove the drain, and when about half the oil has run out, catch the sample by inserting the bottle into the oil stream. The bottle should be at least 3/4 filled. Do not remove the bottle cap until you are ready to take the sample, and recap the bottle immediately after filling. Take care not to confuse samples from different units.
 Or, remove sample with a suction pump by inserting the siphon tube down the dipstick tube or into the sump/reservoir. The siphon tube must be clean by either replacement or rinsing with a solvent and drying. Do not rinse with gasoline or diesel fuel.
 Or, Engines with sample ports (i.e. gauge plugs, probalizer mini-plugs), follow the specific instructions pertaining to the sampling device purchased.

WARRIOR TRACTOR AND EQUIPMENT - HUNTSVILLE

| | | | |
|--|--|---|--|
|  | *Label : 418780 Sample Number : WE0005471 Test Package : MOB 1 Sample Date : 11/20/2023 | Area : CLIFTON%2520FARMS Machine Id : 1FF210PAAPF000028 Component : JOHN%20DEERE Hydraulic System Fluid : (40 GAL) | Machine Age : 500.0 Fluid Age : 500.0 Filter Age : 500.0 Fluid Maintenance : Not Changed Filter Maintenance : None |
|  | *Label : 418781 Sample Number : WE0005468 Test Package : MOB 1 Sample Date : 11/20/2023 | Area : CLIFTON%2520FARMS Machine Id : 1FF210PAAPF000028 Component : JOHN%252520DEERE Diesel Engine Fluid : (8 GAL) | Machine Age : 500.0 Fluid Age : 500.0 Filter Age : 500.0 Fluid Maintenance : Changed Filter Maintenance : Changed |
|  | *Label : 418785 Sample Number : WE0005467 Test Package : MOB 1 Sample Date : 11/20/2023 | Area : CLIFTON%2520FARMS Machine Id : 1FF210PAAPF000028 Component : Left Final Drive Fluid : (3 GAL) | Machine Age : 500.0 Fluid Age : 500.0 Filter Age : 500.0 Fluid Maintenance : N/A Filter Maintenance : N/A |
|  | *Label : 418792 Sample Number : WE0005470 Test Package : MOB 1 Sample Date : 11/20/2023 | Area : CLIFTON%2520FARMS Machine Id : 1FF210PAAPF000028 Component : JOHN%20DEERE Right Final Drive Fluid : (3 GAL) | Machine Age : 500.0 Fluid Age : 500.0 Filter Age : 500.0 Fluid Maintenance : N/A Filter Maintenance : N/A |
|  | *Label : 418795 Sample Number : WE0005469 Test Package : MOB 1 Sample Date : 11/20/2023 | Area : CLIFTON%2520FARMS Machine Id : 1FF210PAAPF000028 Component : JOHN%20DEERE Swing Drive Fluid : (2 GAL) | Machine Age : 500.0 Fluid Age : 500.0 Filter Age : 500.0 Fluid Maintenance : N/A Filter Maintenance : N/A |
|  | *Label : 409002 Sample Number : WE0005620 Test Package : CONST Sample Date : 10/23/2023 | Area : CLIFTON%2520FARMS Machine Id : JOHN DEERE 768L 1DW768LBEMF711470 Component : Front Left Final Drive Fluid : SHELL 80W90 (--- GAL) | Machine Age : 4700.0 Fluid Age : 2110.0 Filter Age : 2068.0 Fluid Maintenance : N/A Filter Maintenance : N/A |



*Label : 418976
 Sample Number : WE0005463
 Test Package : MOB 1
 Sample Date : 11/20/2023

Area CLIFTON%252520FARMS
 Machine Id JOHN%20DEERE 700K 1T0700KXJKF358420
 Component JOHN%20DEERE Diesel Engine
 Fluid (8 GAL)

Machine Age : 1800.0
 Fluid Age : 500.0
 Filter Age : 500.0
 Fluid Maintenance : Changed
 Filter Maintenance : Changed



*Label : 418978
 Sample Number : WE0005476
 Test Package : MOB 1
 Sample Date : 11/20/2023

Area CLIFTON%252520FARMS
 Machine Id JOHN%20DEERE 700K 1T0700KXJKF358420
 Component JOHN%20DEERE Final Drive
 Fluid (8)

Machine Age : 1800.0
 Fluid Age : 500.0
 Filter Age : 500.0
 Fluid Maintenance : Changed
 Filter Maintenance : Changed



*Label : 418980
 Sample Number : WE0005475
 Test Package : MOB 1
 Sample Date : 11/20/2023

Area CLIFTON%252520FARMS
 Machine Id JOHN%20DEERE 700K 1T0700KXJKF358420
 Component JOHN%20DEERE 700K Left Final Drive
 Fluid (8 GAL)

Machine Age : 1800.0
 Fluid Age : 1800.0
 Filter Age : 1800.0
 Fluid Maintenance : N/A
 Filter Maintenance : N/A



*Label : 418982
 Sample Number : WE0005462
 Test Package : MOB 1
 Sample Date : 11/20/2023

Area CLIFTON%252520FARMS
 Machine Id JOHN%20DEERE 700K 1T0700KXJKF358420
 Component JOHN%20DEERE 700K Hydraulic System
 Fluid (40 GAL)

Machine Age : 1800.0
 Fluid Age : 1800.0
 Filter Age : 1800.0
 Fluid Maintenance : N/A
 Filter Maintenance : N/A



*Label : 418986
 Sample Number : WE0005477
 Test Package : MOB 1
 Sample Date : 11/20/2023

Area CLIFTON%252520FARMS
 Machine Id JOHN%20DEERE 700K 1T0700KXJKF358420
 Component Transmission
 Fluid (20 GAL)

Machine Age : 1800.0
 Fluid Age : 1800.0
 Filter Age : 1800.0
 Fluid Maintenance : N/A
 Filter Maintenance : N/A